

#### Description

IP55. Class I. IK10. Marine-grade, die-cast aluminum alloy. 5CE superior corrosion protection including PCS hardware. Silicone CCG® Controlled Compression Gasket. Polycarbonate main lens. Integral driver. Factory-installed LED circuit board. 0-10V Dimming comes standard with luminaire.

Suitable for installation on ceiling or wall over 4" recessed junction box.

Specify product with 7 Digit product code - Finish Color. Accessories, such as mounting, optical, and electrical, must be specified separately.

Example: XXX-XXXX-9004 (Black)

+ XXX-XXXX (Accessory 1)



## **Specifications**

### **Material description**

Body Luminaire body and lens frame constructed in die cast aluminum.

Lens Opal polycarbonate lens.

Colors RAL9004 Black

RAL9007 Grey Metallic

RAL9016 White

RAL8019 Dark Bronze

Gasket Silicone rubber gasket

Fasteners PCS polymer coated stainless steel

Ingress protection IP55
Impact resistance IK10
Corrosion resistance 5CE

#### **Electrical description**

Power supply Integral [ECG] LED driver in 120 or 277 volt. Specify voltage.

Driver / Ballast Integral EC electronic converter

#### **Additional information**

Lifetime  $T_a=25^{\circ}/40^{\circ} L70B50 > 50000h$ 


Listings ETL, UL-1598, CSA-C22.2#250.0. Suitable for Wet Locations.



# Options Light distribution



## **Color temperature Nominal Watt**





## **Configurations**

Light distribution	Part ID	Light source	Delivered lumens	Rated input power	CRI	Weight (lb)
diffused distribution	195-0896	LED-FT-28W / 800 mA - 2700 K	1457.7	31 W	80	8.00
	195-9539	LED-FT-28W / 800 mA - 3000 K	1518.3	31 W	80	8.00
+	195-9540	LED-FT-28W / 800 mA - 4000 K	1585.3	31 W	80	8.00