

DLB239 LED

Wall luminaires surface mounted





Description

IP66, Class I. IK10. Marine-grade, die-cast aluminium alloy. 5CE superior corrosion protection + primer including PCS hardware. Polycarbonate lens. Silicone rubber gasket. Two cable entries.

Integral EC electronic converter. Advanced thermal management protects LEDs while optimising lumens output.



Wall luminaires surface mounted

we-ef

Specifications Material description

Body	Marine-grade die-cast aluminium alloy			
Lens	Polycarbonate main lens			
Colours	RAL9004 Signal black RAL9006 White aluminium RAL9007 Grey aluminium			
Gasket	Silicone rubber gasket			
Fasteners	PCS Polymer Coated Stainless Steel Hardware (unpainted)			
Ingress protection	IP66			
Impact resistance	IK10			
Corrosion resistance	5CE+Primer			

Electrical description

Power supply	230V / 50 Hz
Driver / Ballast	Integral EC electronic converter

Additional information

Lifetime	Ta=40° L70B50 > 50000h
Warranty	The product is supplied with 10-year warranty. Please refer to the LED Warranty Statement located on www.we-ef.com for further details.



DLB239 LED

Wall luminaires surface mounted



Options Light distribution

Light distribution	Colour temperature	Nominal Watt		
+ diffused distribution	3000 K	27 W		
	4000 K			
	2700 K			

WE-EF LIGHTING Pty Ltd 47 Tarnard Drive, 3195 Braeside, Victoria - Phone: +61 3 8587 0444 - Fax: +61 3 8587 0499 info.australia@we-ef.com - https://we-ef.com/aus Subject to technical changes and errors. - Generated on 18/07/2025

DLB239 LED

Wall luminaires surface mounted

we-ef

Configurations

Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI	Weight (kg)
diffuse of distuits wish	105 0000				00	2 70
diffused distribution	195-0900	LED-FT-28W / 800 mA - 2700 K		31 W	80	3.70
	195-9545	LED-FT-28W / 800 mA - 3000 K	1198.1	31 W	80	3.70
+	195-9546	LED-FT-28W / 800 mA - 4000 K	1250.9	31 W	80	3.70