


**Wall luminaires surface mounted****Description**

IP66, Class I. IK10. Marine-grade, die-cast aluminium alloy. 5CE superior corrosion protection + primer including PCS hardware. Polycarbonate lens. Silicone rubber gasket. Two cable entries.

Integral EC electronic converter. Advanced thermal management protects LEDs while optimising lumens output.

**Specifications****Material description**


Body	Marine-grade die-cast aluminium alloy
Lens	Polycarbonate main lens
Colours	 RAL9004 Signal black  RAL9006 White aluminium  RAL9007 Grey aluminium
Gasket	Silicone rubber gasket
Fasteners	PCS Polymer Coated Stainless Steel Hardware (unpainted)
Ingress protection	IP66
Impact resistance	IK10
Corrosion resistance	5CE+Primer

**Electrical description**

Power supply	230V / 50 Hz
Driver / Ballast	Integral EC electronic converter

**Additional information**

Lifetime	T <sub>a</sub> =40° L70B50 > 50000h
Warranty	The product is supplied with 10-year warranty. Please refer to the LED Warranty Statement located on <a href="http://www.we-ef.com">www.we-ef.com</a> for further details.

**Wall luminaires surface mounted****Options****Light distribution**

+ diffused distribution

**Colour temperature**

3000 K


4000 K

2700 K

**Nominal Watt**

27 W

**Wall luminaires surface mounted****Configurations**

Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI	Weight (kg)
diffused distribution 	195-0898	LED-FT-28W / 800 mA - 2700 K	1150.2	31 W	80	3.70
	195-9542	LED-FT-28W / 800 mA - 3000 K	1198.1	31 W	80	3.70
	195-9543	LED-FT-28W / 800 mA - 4000 K	1250.9	31 W	80	3.70