**Description**

IP67, Class I. IK07. Stainless steel construction including PCS hardware. Silicone rubber gasket. Safety glass lens; max. load 5 tonnes. Luminaire can be driven over at low speed. Factory-sealed termination chamber complete with cable gland and 1,5 m of flexible PVC free cable. Cable gland with spiral cable bending protection.

'No tool' removable gear/reflector tray. Anodised aluminium reflector.

Luminaire requires installation blockout and sealable junction box, which are included in supply.

2700 K option available on request.

**IMPORTANT!** Inground blockouts must be installed with effective drainage, watch **[here](https://vimeo.com/672613058)**.

**Inground luminaires****Specifications****Material description**

Body	Stainless steel inground section. Die-cast hood made from marine-grade aluminium alloy
Lens	Safety glass lens
Colours	 RAL9004 Signal black  RAL9006 White aluminium  RAL9007 Grey aluminium
Gasket	Silicone rubber gasket
Fasteners	PCS Polymer Coated Stainless Steel Hardware (unpainted)
Ingress protection	IP67
Impact resistance	IK09
Corrosion resistance	5CE. 5CE+Primer optional


**Electrical description**

Power supply	230V / 50 Hz
Driver / Ballast	Integral EC electronic converter
Termination	Junction box supplied

**Additional information**

Warranty	The product is supplied with 10-year warranty. Please refer to the LED Warranty Statement located on <a href="http://www.we-ef.com">www.we-ef.com</a> for further details.
----------	--

Warranty void if installed without proper drainage.

**Options****Light distribution**

symmetric, medium beam [M]



symmetric, very narrow beam [EE]



symmetric, very narrow beam, sharp cut-off [EES]

**Colour temperature**




3000 K



4000 K


**42 W**

## Configurations

Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI	Weight (kg)
symmetric, medium beam [M] 	185-7720	LED-24/36W / 500 mA - 3000 K	3510.1	39 W	80	18.70
	185-7723	LED-24/36W / 500 mA - 4000 K	3755	39 W	80	18.70
symmetric, very narrow beam [EE] 	185-7721	LED-24/36W / 500 mA - 3000 K	3602.2	39 W	80	18.70
	185-7724	LED-24/36W / 500 mA - 4000 K	3853.5	39 W	80	18.70
symmetric, very narrow beam, sharp cut-off [EES] 	185-7722	LED-24/36W / 500 mA - 3000 K	3788.6	39 W	80	18.70
	185-7725	LED-24/36W / 500 mA - 4000 K	4052.9	39 W	80	18.70

**Mounting Accessories****Installation cover**

Description	Part ID	C1
Installation cover BE	185-0326	300



C1