


## ESC340-FS LED

### Inground luminaires

**we-ef**



#### Description

IP67, Class I. IK07. Stainless steel construction including PCS hardware. Silicone rubber gasket. Safety glass lens; max. load 5 tonnes. Luminaire can be driven over at low speed. Factory-sealed termination chamber complete with cable gland and 1,5 m of flexible PVC free cable. Cable gland with spiral cable bending protection.

'No tool' removable gear/reflector tray. Anodised aluminium reflector.

Luminaire requires installation blackout and sealable junction box, which are included in supply.

2700 K option available on request.

IMPORTANT! Inground blockouts must be installed with effective drainage, watch [here](https://vimeo.com/672613058).




#### WE-EF LIGHTING Pty Ltd

47 Tarnard Drive, 3195 Braeside, Victoria - Phone: +61 3 8587 0444 - Fax: +61 3 8587 0499

info.australia@we-ef.com - <https://we-ef.com/aus>

Subject to technical changes and errors. - Generated on 16/08/2025

**Specifications****Material description**

Body	Stainless steel inground section. Die-cast hood made from marine-grade aluminium alloy	
Lens	Safety glass lens	
Colours		RAL9004 Signal black
		RAL9006 White aluminium
		RAL9007 Grey aluminium
Gasket	Silicone rubber gasket	
Fasteners	PCS Polymer Coated Stainless Steel Hardware (unpainted)	
Ingress protection	IP67	
Impact resistance	IK09	
Corrosion resistance	5CE. 5CE+Primer optional	

**Electrical description**

Power supply	230V / 50 Hz
Driver / Ballast	Integral EC electronic converter
Termination	Junction box supplied

**Additional information**

Warranty	The product is supplied with 10-year warranty. Please refer to the LED Warranty Statement located on <a href="http://www.we-ef.com">www.we-ef.com</a> for further details.
	Warranty void if installed without proper drainage.

ESC340-FS LED



Inground luminaires

Options

Light distribution



symmetric, medium beam [M]



symmetric, very narrow beam [EE]



symmetric, very narrow beam, sharp cut-off [EES]

Colour temperature



3000 K






4000 K

Nominal Watt

42 W

## Configurations

Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI	Weight (kg)
symmetric, medium beam [M] 	185-7720	LED-24/36W / 500 mA - 3000 K	3510.1	39 W	80	18.70
	185-7723	LED-24/36W / 500 mA - 4000 K	3755	39 W	80	18.70
symmetric, very narrow beam [EE] 	185-7721	LED-24/36W / 500 mA - 3000 K	3602.2	39 W	80	18.70
	185-7724	LED-24/36W / 500 mA - 4000 K	3853.5	39 W	80	18.70
symmetric, very narrow beam, sharp cut-off [EES] 	185-7722	LED-24/36W / 500 mA - 3000 K	3788.6	39 W	80	18.70
	185-7725	LED-24/36W / 500 mA - 4000 K	4052.9	39 W	80	18.70

Mounting Accessories

Installation cover

Description	Part ID	C1
Installation cover BE	185-0326	300

