

Description

IP67, Class I. IK07. Stainless steel construction including PCS hardware. Silicone rubber gasket. Safety glass lens; max. load 5 tonnes. Luminaire can be driven over at low speed. Factory-sealed termination chamber complete with cable gland and 1,5 m of flexible PVC free cable. Cable gland with spiral cable bending protection.

'No tool' removable gear/reflector tray. Anodised aluminium reflector.

Luminaire requires installation blackout and sealable junction box, which are included in supply.

2700 K option available on request.

IMPORTANT! Inground blockouts must be installed with effective drainage, watch [here](https://vimeo.com/672613058).

Specifications

Material description

Body	Stainless steel inground section. Die-cast hood made from marine-grade aluminium alloy
Lens	Safety glass lens
Colours	<div><div></div> RAL9004 Signal black</div> <div><div></div> RAL9006 White aluminium</div> <div><div></div> RAL9007 Grey aluminium</div>
Gasket	Silicone rubber gasket
Fasteners	PCS Polymer Coated Stainless Steel Hardware (unpainted)
Ingress protection	IP67
Impact resistance	IK09
Corrosion resistance	5CE. 5CE+Primer optional

Electrical description

Power supply	230V / 50 Hz
Driver / Ballast	Integral EC electronic converter
Termination	Junction box supplied

Additional information

Warranty	The product is supplied with 10-year warranty. Please refer to the LED Warranty Statement located on www.we-ef.com for further details.
	Warranty void if installed without proper drainage.

Options

Light distribution

Colour temperature

Nominal Watt



symmetric, medium beam [M]




3000 K

42 W



symmetric, very narrow beam [EE]






4000 K



symmetric, very narrow beam, sharp cut-off [EES]

Configurations

Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI	Weight (kg)
symmetric, medium beam [M] 	185-7720	LED-24/36W / 500 mA - 3000 K	3510.1	39 W	80	18.70
	185-7723	LED-24/36W / 500 mA - 4000 K	3755	39 W	80	18.70
symmetric, very narrow beam [EE] 	185-7721	LED-24/36W / 500 mA - 3000 K	3602.2	39 W	80	18.70
	185-7724	LED-24/36W / 500 mA - 4000 K	3853.5	39 W	80	18.70
symmetric, very narrow beam, sharp cut-off [EES] 	185-7722	LED-24/36W / 500 mA - 3000 K	3788.6	39 W	80	18.70
	185-7725	LED-24/36W / 500 mA - 4000 K	4052.9	39 W	80	18.70

Mounting Accessories

Installation cover

Description	Part ID	C1
Installation cover BE	185-0326	300

