**Description**

IP67, Class I. IK10+. Stainless steel construction including PCS hardware. Silicone rubber gasket. Safety glass lens; max. load 5 tonnes. Luminaire can be driven over at low speed. Factory-sealed termination chamber complete with cable gland and 1,5 m of flexible PVC free cable. Cable gland with spiral cable bending protection.

Integral EC electronic converter.

Luminaire requires installation blackout and sealable junction box, which are included in supply.


ETC339 LED



Inground luminaires

Specifications

Material description

Colours	 Stainless Steel
Ingress protection	IP67
Impact resistance	IK10+

Electrical description

Additional information

Lifetime	Ta=40° L90B10 > 90000h
----------	------------------------

## ETC339 LED

Inground luminaires

**we-ef**

### Options

Light distribution   Colour temperature   Nominal Watt

#### WE-EF LIGHTING Pty Ltd

47 Tarnard Drive, 3195 Braeside, Victoria - Phone: +61 3 8587 0444 - Fax: +61 3 8587 0499  
info.australia@we-ef.com - <https://we-ef.com/aus>

Subject to technical changes and errors. - Generated on 19/04/2025

ETC339 LED

Inground luminaires




Configurations

Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI	Weight (kg)
--------------------	---------	--------------	--------------	-------------------	-----	-------------

Mounting Accessories

Installation cover

Description	Part ID	C1
Installation cover BE	185-0325	250



Electrical Accessories

Sealable junction box

Description	Part ID	C1	M1	M2
Sealable junction box SJB130	185-1624	146	Ø 10	Ø 12 - 19

