

Description

IP67, Class I. IK09. Marine-grade, all aluminium construction. 5CE superior corrosion protection + primer including PCS hardware. Silicone rubber gasket. PMMA main lens. Linear PMMA LED lens. 1.2 m connecting cable, UV stabilized, PVC free. Luminaire is factory-sealed and does not need to be opened during installation, and can be tilted up to 180°.

Separate LED driver with DALI interface.

we-ef

Wall luminaires surface mounted

Specifications Material description

Body Marine-grade, all-aluminium construction

Lens PMMA

Colours RAL9004 Signal black

RAL9006 White aluminium
RAL9007 Grey aluminium

Gasket Silicone rubber gasket

Fasteners PCS Polymer Coated Stainless Steel Hardware (unpainted)

Ingress protection IP67
Impact resistance IK09

Corrosion resistance 5CE+Primer

Electrical description

Power supply 230V / 50 Hz

Driver / Ballast Separate LED driver with DALI Interface

Additional information

Lifetime $Ta=40^{\circ} L90B10 > 90000h$

Warranty The product is supplied with 10-year warranty. Please refer to the LED Warranty Statement

located on www.we-ef.com for further details.



Wall luminaires surface mounted

Options

Light distribution



symmetric linear, medium beam [LM]



symmetric linear, narrow beam [LE]



symmetric linear, very narrow beam [LEE]



symmetric linear, wide beam [LB]



symmetric linear, wide beam [LB/IW - Honeycomb]




symmetric linear, medium beam [LM/IW - Honeycomb]



symmetric linear, narrow beam [LE/IW - Honeycomb]









Configurations

Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI	Weight (kg)
symmetric linear, medium beam [LM/ IW - Honeycomb]	187-0478	LED-16/10W / 225 mA - 3000 K	534.4	13 W	80	1.20
	187-0479	LED-16/10W / 225 mA - 4000 K	534.4	13 W	80	1.20
	187-0577	LED-16/10W / 225 mA - 2700 K	534.4	13 W	80	1.20
symmetric linear, medium beam [LM]	187-0001	LED-16/10W / 225 mA - 3000 K	1070.2	13 W	80	1.20
	187-0031	LED-16/10W / 225 mA - 4000 K	1070.2	13 W	80	1.20
	187-0459	LED-16/10W / 225 mA - 2700 K	1024.9	13 W	80	1.20
symmetric linear, narrow beam [LE/ IW - Honeycomb]	187-0480	LED-16/10W / 225 mA - 3000 K	556.8	13 W	80	1.20
	187-0481	LED-16/10W / 225 mA - 4000 K	556.8	13 W	80	1.20
	187-0578	LED-16/10W / 225 mA - 2700 K	556.8	13 W	80	1.20
symmetric linear, narrow beam [LE]	187-0005	LED-16/10W / 225 mA - 3000 K	1050.6	13 W	80	1.20
	187-0032	LED-16/10W / 225 mA - 4000 K	1050.6	13 W	80	1.20
	187-0532	LED-16/10W / 225 mA - 2700 K	1050.6	13 W	80	1.20
symmetric linear, very narrow beam [LEE]	187-0009	LED-16/10W / 225 mA - 3000 K	1203	13 W	80	1.20
	187-0033	LED-16/10W / 225 mA - 4000 K	1203	13 W	80	1.20
	187-0533	LED-16/10W / 225 mA - 2700 K	1203	13 W	80	1.20
symmetric linear, wide beam [LB/IW - Honeycomb]	187-0476	LED-16/10W / 225 mA - 3000 K	425.8	13 W	80	1.20
	187-0477	LED-16/10W / 225 mA - 4000 K	425.8	13 W	80	1.20
	187-0576	LED-16/10W / 225 mA - 2700 K	425.8	13 W	80	1.20
symmetric linear, wide beam [LB]	187-0023	LED-16/10W / 225 mA - 3000 K	957.9	13 W	80	1.20
	187-0034	LED-16/10W / 225 mA - 4000 K	957.9	13 W	80	1.20
	187-0531	LED-16/10W / 225 mA - 2700 K	957.9	13 W	80	1.20

VLR110



Wall luminaires surface mounted

Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI Weight (kg)

