




**Description**

IP67, Class I. IK09. Marine-grade, all aluminium construction. 5CE superior corrosion protection + primer including PCS hardware. PMMA cover. Silicone rubber gasket. Linear PMMA LED lens. 1.2 m connecting cable, UV stabilized, PVC free. Luminaire is factory sealed and does not need to be opened during installation and can be tilted up to 180°. Integral LED driver with DALI interface.

Separate LED driver on request.

**Wall luminaires surface mounted****Specifications****Material description**

---

|                      |   |
|----------------------|---|
| Body                 | Marine-grade, all-aluminium construction  |
| Lens                 | PMMA  |
| Colours              |  RAL9004 Signal black<br> RAL9006 White aluminium<br> RAL9007 Grey aluminium |
| Gasket               | Silicone rubber gasket  |
| Fasteners            | PCS Polymer Coated Stainless Steel Hardware (unpainted)   |
| Ingress protection   | IP67  |
| Impact resistance    | IK09  |
| Corrosion resistance | 5CE+Primer  |

---

**Electrical description**

---

|                  |   |
|------------------|---|
| Power supply     | 230V / 50 Hz                            |
| Driver / Ballast | Integral LED driver with DALI Interface |

---

**Additional information**

---

|          |  |
|----------|--|
| Lifetime | Ta=40° L90B10 > 90000h   |
| Warranty | The product is supplied with 10-year warranty. Please refer to the LED Warranty Statement located on <a href="http://www.we-ef.com">www.we-ef.com</a> for further details. |

---

# VLR130

## Wall luminaires surface mounted

**we-ef**

### Options

#### Light distribution



symmetric linear, medium beam [LM]



symmetric linear, narrow beam [LE]



symmetric linear, very narrow beam [LEE]



symmetric linear, wide beam [LB]



symmetric linear, wide beam [LB/IW - Honeycomb]



symmetric linear, medium beam [LM/IW - Honeycomb]



symmetric linear, narrow beam [LE/IW - Honeycomb]

#### Colour temperature



3000 K



4000 K



2700 K








#### Nominal Watt

27 W

0 W

## Wall luminaires surface mounted

## Configurations

| Light distribution   | Part ID  | Light source                 | Rated lumens | Rated input power | CRI | Weight (kg) |
|--|----------|------------------------------|--------------|-------------------|-----|-------------|
| symmetric linear, medium beam [LM/<br>IW - Honeycomb]<br>  | 187-0498 | LED-48/30W / 225 mA - 3000 K | 1603.2       | 33.5 W            | 80  | 3.25        |
|  | 187-0499 | LED-48/30W / 225 mA - 4000 K | 1603.2       | 33.5 W            | 80  | 3.25        |
|  | 187-0587 | LED-48/30W / 225 mA - 2700 K | 1603.2       | 33.5 W            | 80  | 3.25        |
| symmetric linear, medium beam [LM]<br>                     | 187-0003 | LED-48/30W / 225 mA - 3000 K | 3210.6       | 33.5 W            | 80  | 3.25        |
|  | 187-0039 | LED-48/30W / 225 mA - 4000 K | 3210.6       | 33.5 W            | 80  | 3.25        |
|  | 187-0538 | LED-48/30W / 225 mA - 2700 K | 3210.6       | 33.5 W            | 80  | 3.25        |
| symmetric linear, narrow beam [LE/<br>IW - Honeycomb]<br> | 187-0500 | LED-48/30W / 225 mA - 3000 K | 1670.5       | 33.5 W            | 80  | 3.25        |
|  | 187-0501 | LED-48/30W / 225 mA - 4000 K | 1670.5       | 33.5 W            | 80  | 3.25        |
|  | 187-0588 | LED-48/30W / 225 mA - 2700 K | 1670.5       | 33.5 W            | 80  | 3.25        |
| symmetric linear, narrow beam [LE]<br>                   | 187-0007 | LED-48/30W / 225 mA - 3000 K | 3151.9       | 33.5 W            | 80  | 3.25        |
|  | 187-0040 | LED-48/30W / 225 mA - 4000 K | 3151.9       | 33.5 W            | 80  | 3.25        |
|  | 187-0539 | LED-48/30W / 225 mA - 2700 K | 3151.9       | 33.5 W            | 80  | 3.25        |
| symmetric linear, very narrow beam<br>[LEE]<br>          | 187-0011 | LED-48/30W / 225 mA - 3000 K | 3608.9       | 33.5 W            | 80  | 3.25        |
|  | 187-0041 | LED-48/30W / 225 mA - 4000 K | 3608.9       | 33.5 W            | 80  | 3.25        |
|  | 187-0540 | LED-48/30W / 225 mA - 2700 K | 3608.9       | 33.5 W            | 80  | 3.25        |
| symmetric linear, wide beam [LB/IW -<br>Honeycomb]<br>   | 187-0496 | LED-48/30W / 225 mA - 3000 K | 1277.3       | 33.5 W            | 80  | 3.25        |
|  | 187-0497 | LED-48/30W / 225 mA - 4000 K | 1277.3       | 33.5 W            | 80  | 3.25        |
|  | 187-0586 | LED-48/30W / 225 mA - 2700 K | 1277.3       | 33.5 W            | 80  | 3.25        |
| symmetric linear, wide beam [LB]<br>                     | 187-0025 | LED-48/30W / 225 mA - 3000 K | 2873.6       | 33.5 W            | 80  | 3.25        |
|  | 187-0042 | LED-48/30W / 225 mA - 4000 K | 2873.6       | 33.5 W            | 80  | 3.25        |
|  | 187-0537 | LED-48/30W / 225 mA - 2700 K | 2873.6       | 33.5 W            | 80  | 3.25        |

**VLR130**

**Wall luminaires surface mounted**

**WE-EF LIGHTING Pty Ltd**

6/13 Downard Street, 3195 Braeside, Victoria

Phone: +61 3 8587 0444

Fax: +61 3 8587 0499

info.australia@we-ef.com

<https://we-ef.com/aus>

Subject to technical changes and errors.

Generated on 23/10/2024