

**Description**

IP67. Class I. IK09. Marine-grade, all aluminum construction. 5CE superior corrosion protection including PCS hardware. Silicone CCG® Controlled Compression Gasket. Linear PMMA LED lens, PMMA cover. 4 ft connecting cable, UV stabilized, PVC free. Integral LED driver; separate LED driver available instead, on request at time of order. 0-10V Dimming comes standard with luminaire. Luminaire is factory-sealed and does not need to be opened during installation and can be tilted up to 180°.

Specify product with 7 Digit product code - Finish Color. Accessories, such as mounting, optical, and electrical, must be specified separately.

Example: XXX-XXXX-9004 (Black)  
+ XXX-XXXX (Accessory 1)

## Surface Mounted Wall Luminaires

## Specifications

## Material description

Body	Marine-grade, all-aluminium construction
Lens	PMMA
Colors	<div style="display: flex; flex-direction: column; gap: 5px;"> <div style="display: flex; align-items: center;"> <div style="width: 20px; height: 15px; background-color: black; margin-right: 5px;"></div> <span>RAL9004 Black</span> </div> <div style="display: flex; align-items: center;"> <div style="width: 20px; height: 15px; background-color: #808080; margin-right: 5px;"></div> <span>RAL9007 Grey Metallic</span> </div> <div style="display: flex; align-items: center;"> <div style="width: 20px; height: 15px; background-color: white; margin-right: 5px;"></div> <span>RAL9016 White</span> </div> <div style="display: flex; align-items: center;"> <div style="width: 20px; height: 15px; background-color: #654321; margin-right: 5px;"></div> <span>RAL8019 Dark Bronze</span> </div> </div>
Gasket	Silicone rubber gasket
Fasteners	PCS Polymer Coated Stainless Steel Hardware
Ingress protection	IP67
Impact resistance	IK09
Corrosion resistance	5CE

## Electrical description

Power supply	Integral [ECG] electronic driver 120V-277V. 0-10V dimmable, to be specified with order.
Driver / Ballast	Integral 0-10V LED driver

## Additional information

Lifetime	Ta=25°/40° L90B10 > 90000h
Listings	ETL, UL-1598, CSA-C22.2#250.0. Suitable for Wet Locations. Meets ANSI C136.31 - 3G Vibration Rating for Bridge and Overpass Applications.

## WE-EF LIGHTING USA, LLC

410-D Keystone Drive, 15086 Warrendale, PA 15086 - Phone: +1 724 742 0030

customersupport.usa@we-ef.com - <https://we-ef.com/us>

Subject to technical changes and errors. - Generated on 11/23/2024

# VLR130

## Surface Mounted Wall Luminaires



### Options

#### Light distribution

#### Color temperature

#### Nominal Watt



symmetric linear, medium beam [LM]



3000 K

27 W

0 W



symmetric linear, narrow beam [LN]



4000 K



symmetric linear, very narrow beam [LVN]



2700 K



symmetric linear, wide beam [LW]



symmetric linear, wide beam [LW/IW]



symmetric linear, medium beam [LM/IW]



symmetric linear, narrow beam [LN/IW]

#### WE-EF LIGHTING USA, LLC








410-D Keystone Drive, 15086 Warrendale, PA 15086 - Phone: +1 724 742 0030

customersupport.usa@we-ef.com - <https://we-ef.com/us>

Subject to technical changes and errors. - Generated on 11/23/2024

## Surface Mounted Wall Luminaires

## Configurations

Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI	Weight (lb)
symmetric linear, medium beam [LM/IW] 	187-0498	LED-48/30W / 225 mA - 3000 K	1603.2	33.5 W	80	3.25
	187-0499	LED-48/30W / 225 mA - 4000 K	1603.2	33.5 W	80	3.25
	187-0587	LED-48/30W / 225 mA - 2700 K	1603.2	33.5 W	80	3.25
symmetric linear, medium beam [LM] 	187-0003	LED-48/30W / 225 mA - 3000 K	3210.6	33.5 W	80	3.25
	187-0039	LED-48/30W / 225 mA - 4000 K	3210.6	33.5 W	80	3.25
	187-0538	LED-48/30W / 225 mA - 2700 K	3210.6	33.5 W	80	3.25
symmetric linear, narrow beam [LN/IW] 	187-0500	LED-48/30W / 225 mA - 3000 K	1670.5	33.5 W	80	3.25
	187-0501	LED-48/30W / 225 mA - 4000 K	1670.5	33.5 W	80	3.25
	187-0588	LED-48/30W / 225 mA - 2700 K	1670.5	33.5 W	80	3.25
symmetric linear, narrow beam [LN] 	187-0007	LED-48/30W / 225 mA - 3000 K	3151.9	33.5 W	80	3.25
	187-0040	LED-48/30W / 225 mA - 4000 K	3151.9	33.5 W	80	3.25
	187-0539	LED-48/30W / 225 mA - 2700 K	3151.9	33.5 W	80	3.25
symmetric linear, very narrow beam [LVN] 	187-0011	LED-48/30W / 225 mA - 3000 K	3608.9	33.5 W	80	3.25
	187-0041	LED-48/30W / 225 mA - 4000 K	3608.9	33.5 W	80	3.25
	187-0540	LED-48/30W / 225 mA - 2700 K	3608.9	33.5 W	80	3.25
symmetric linear, wide beam [LW/IW] 	187-0496	LED-48/30W / 225 mA - 3000 K	1277.3	33.5 W	80	3.25
	187-0497	LED-48/30W / 225 mA - 4000 K	1277.3	33.5 W	80	3.25
	187-0586	LED-48/30W / 225 mA - 2700 K	1277.3	33.5 W	80	3.25
symmetric linear, wide beam [LW] 	187-0025	LED-48/30W / 225 mA - 3000 K	2873.6	33.5 W	80	3.25
	187-0042	LED-48/30W / 225 mA - 4000 K	2873.6	33.5 W	80	3.25

## WE-EF LIGHTING USA, LLC


410-D Keystone Drive, 15086 Warrendale, PA 15086 - Phone: +1 724 742 0030

customersupport.usa@we-ef.com - <https://we-ef.com/us>

Subject to technical changes and errors. - Generated on 11/23/2024

# VLR130

## Surface Mounted Wall Luminaires

Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI	Weight (lb)
	187-0537	LED-48/30W / 225 mA - 2700 K	2873.6	33.5 W	80	3.25

**WE-EF LIGHTING USA, LLC**

410-D Keystone Drive, 15086 Warrendale, PA 15086 - Phone: +1 724 742 0030  
customersupport.usa@we-ef.com - <https://we-ef.com/us>  
Subject to technical changes and errors. - Generated on 11/23/2024