





#### **Description**

IP67. Class I. IK09. Marine-grade, all aluminum construction. 5CE superior corrosion protection including PCS hardware. Silicone CCG® Controlled Compression Gasket. Linear PMMA LED lens, PMMA cover. 4 ft connecting cable, UV stabilized, PVC free. Integral LED driver; separate LED driver available instead, on request at time of order. 0-10V Dimming comes standard with luminaire. Luminaire is factory-sealed and does not need to be opened during installation and can be tilted up to 180°.

Specify product with 7 Digit product code - Finish Color. Accessories, such as mounting, optical, and electrical, must be specified separately.

Example: XXX-XXXX-9004 (Black) + XXX-XXXX (Accessory 1)



#### **Surface Mounted Wall Luminaires**

# **Specifications**

## **Material description**

Body Marine-grade, all-aluminium construction

Lens PMMA

Colors RAL9004 Black

RAL9007 Grey Metallic

RAL9016 White

RAL8019 Dark Bronze

Gasket Silicone rubber gasket

Fasteners PCS Polymer Coated Stainless Steel Hardware

Ingress protection IP67
Impact resistance IK09
Corrosion resistance 5CE

#### **Electrical description**

Power supply Integral [ECG] electronic driver 120V-277V. 0-10V dimmable, to be specified with order.

Driver / Ballast LED driver with 0-10V Interface

#### **Additional information**

Lifetime  $Ta=25^{\circ}/40^{\circ} L90B10 > 90000h$ 

Listings ETL Listed. Suitable for wet locations.

# we-ef

#### **Surface Mounted Wall Luminaires**

# **Options Light distribution**



symmetric linear, medium beam [LM]



symmetric linear, narrow beam [LN]



symmetric linear, wide beam [LW]



symmetric linear, very narrow beam [LVN]



symmetric linear, wide beam [LW/IW]



symmetric linear, medium beam [LM/IW]



symmetric linear, narrow beam [LN/IW]



35 W

0 W

3000 K

4000 K

2700 K

# **Surface Mounted Wall Luminaires**

# **Configurations**

Light distribution	Part ID	Light source	Delivered lumens	Rated input power	CRI	Weight (lb)
symmetric linear, medium beam [LM/IW]	187-0508	LED-64/40W / 225 mA - 3000 K	2137.6	44 W	80	8.82
	187-0509	LED-64/40W / 225 mA - 4000 K	2137.6	44 W	80	8.82
	187-0592	LED-64/40W / 225 mA - 2700 K	2137.6	44 W	80	8.82
symmetric linear, medium beam [LM]	187-0004	LED-64/40W / 225 mA - 3000 K	4280.8	44 W	80	8.82
	187-0043	LED-64/40W / 225 mA - 4000 K	4280.8	44 W	80	8.82
	187-0542	LED-64/40W / 225 mA - 2700 K	4280.8	44 W	80	8.82
symmetric linear, narrow beam [LN/ IW]	187-0510	LED-64/40W / 225 mA - 3000 K	2227.4	44 W	80	8.82
	187-0511	LED-64/40W / 225 mA - 4000 K	2227.4	44 W	80	8.82
	187-0593	LED-64/40W / 225 mA - 2700 K	2227.4	44 W	80	8.82
symmetric linear, narrow beam [LN]	187-0008	LED-64/40W / 225 mA - 3000 K	4202.5	44 W	80	8.82
	187-0044	LED-64/40W / 225 mA - 4000 K	4202.5	44 W	80	8.82
	187-0543	LED-64/40W / 225 mA - 2700 K	4202.5	44 W	80	8.82
symmetric linear, very narrow beam [LVN]	187-0012	LED-64/40W / 225 mA - 3000 K	4811.9	44 W	80	8.82
	187-0045	LED-64/40W / 225 mA - 4000 K	4811.9	44 W	80	8.82
	187-0544	LED-64/40W / 225 mA - 2700 K	4811.9	44 W	80	8.82
symmetric linear, wide beam [LW/IW]	187-0506	LED-64/40W / 225 mA - 3000 K	1703	44 W	80	8.82
	187-0507	LED-64/40W / 225 mA - 4000 K	1703	44 W	80	8.82
	187-0591	LED-64/40W / 225 mA - 2700 K	1703	44 W	80	8.82
symmetric linear, wide beam [LW]	187-0026	LED-64/40W / 225 mA - 3000 K	3831.5	44 W	80	8.82
	187-0046	LED-64/40W / 225 mA - 4000 K	3831.5	44 W	80	8.82

## **VLR140**



## **Surface Mounted Wall Luminaires**

Light distribution	Part ID	Light source	Delivered lumens	Rated input power	CRI	Weight (lb)
	187-0541	LED-64/40W / 225 mA - 2700 K	3831.5	44 W	80	8.82