




Description

IP66, Class I. IK07. Marine-grade, die-cast aluminium alloy. 5CE superior corrosion protection including PCS hardware. Silicone CCG_R_ Controlled Compression Gasket. Safety glass lens. Integral EC electronic converter in thermally separated compartment. CAD-optimised optics for superior illumination and glare control. OLC_R_ One LED Concept. Factory installed LED circuit board. The luminaire is factory- sealed and does not need to be opened during the installation. Optional 2200 K version available, except version [A20]. To be specified at time of ordering.

Projectors**Specifications****Material description**

Body	Marine-grade, die-cast aluminium alloy
Lens	Safety glass lens
Colours	 RAL9004 Signal black  RAL9006 White aluminium  RAL9007 Grey aluminium
Gasket	Silicone CCG® Controlled Compression Gasket
Fasteners	PCS Polymer Coated Stainless Steel Hardware (unpainted)
Ingress protection	IP66
Impact resistance	IK07
Corrosion resistance	5CE+Primer

Electrical description

Power supply	230V / 50 Hz
Driver / Ballast	Integral EC electronic converter in thermally-separated compartment

Additional information

Lifetime	Ta=40° L90B10 > 90000h
Warranty	The product is supplied with 10-year warranty. Please refer to the LED Warranty Statement located on www.we-ef.com for further details.

FLD111 LED #3

Projectors

Options

Light distribution



symmetric, medium beam [M]



symmetric, very narrow beam [EE]



symmetric, very narrow beam, sharp cut-off [EES]



wallwash



symmetric, wide beam [B]

Colour temperature



3000 K



4000 K








2700 K

Nominal Watt

8 W

0 W


Configurations

Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI	Weight (kg)
symmetric, medium beam [M] 	145-0309	LED-3/6W / 700 mA - 2700 K	648.3	7.5 W	80	1.60
	145-9791	LED-3/6W / 700 mA - 3000 K	696.3	7.5 W	80	1.60
	145-9795	LED-3/6W / 700 mA - 4000 K	744.3	7.5 W	80	1.60
symmetric, very narrow beam [EE] 	145-0310	LED-3/6W / 700 mA - 2700 K	605.8	7.5 W	80	1.60
	145-9792	LED-3/6W / 700 mA - 3000 K	650.7	7.5 W	80	1.60
	145-9796	LED-3/6W / 700 mA - 4000 K	695.6	7.5 W	80	1.60
symmetric, very narrow beam, sharp cut-off [EES] 	145-0311	LED-3/6W / 700 mA - 2700 K	652.3	7.5 W	80	1.60
	145-9793	LED-3/6W / 700 mA - 3000 K	700.7	7.5 W	80	1.60
	145-9797	LED-3/6W / 700 mA - 4000 K	749	7.5 W	80	1.60
symmetric, wide beam [B] 	145-7088	LED-3/6W / 700 mA - 3000 K	584.9	7.5 W	80	1.60
	145-7089	LED-3/6W / 700 mA - 4000 K	625.3	7.5 W	80	1.60
	145-7104	LED-3/6W / 700 mA - 2700 K	464.4	8 W	80	1.60
wallwash 	145-9791+145-9846	LED-3/6W / 700 mA - 3000 K	458.2	7.5 W	80	1.60
	145-9795+145-9846	LED-3/6W / 700 mA - 4000 K	489.7	7.5 W	80	1.60

Mounting Accessories

Ground spike EF

Description	Part ID	H1	Weight (kg)
Ground spike EF1-2/M5 for FLD100	145-9196	270	1.00




Projectors

Optical Accessories


Optical Adaptor

Description	Part ID	A	C1
External optical adaptor EA	145-9830	53	91




Glare shield

Description	Part ID	A	C1
Glare shield ES	145-9831	53	91




Projectors**Snoot**

Description	Part ID	A	C1
Snoot ET	145-9832	53	91

**Linear spread lens**


Description	Part ID	C1
EO-180-FLD111-LED	145-9833	68



Projectors

Surface wash lens

Description	Part ID	C1
EO-360-FLD111-LED	145-9834	68



Wallwash lens

Description	Part ID	C1
Wallwash lens IO-20	145-9846	71

