



Inground Luminaires



Inground Luminaires**Specifications****Material description**

| | |
|----------------------|--|
| Body | Luminaire body constructed of deep drawn stainless steel. Outer housing composite material. |
| Lens | 5/8 in thick Antislip Coating ASC tempered glass lens (Slip Resistance Class R10), max load 5 tonnes |
| Colors |  Stainless Steel |
| Gasket | Silicone rubber gasket |
| Fasteners | PCS polymer coated stainless steel |
| Ingress protection | IP69K - HIGHEST PROTECTION RATING AVAILABLE |
| Impact resistance | IK10+ |
| Corrosion resistance | 5CE |

Electrical description

| | |
|--------------|--|
| Power supply | Integral [ECG] electronic driver 120V-277V |
| Termination | Factory sealed termination chamber |

Additional information

| | |
|----------|--|
| Lifetime | Ta=25°/40° L90B10 > 90000h |
| Listings | ETL, UL-1598, CSA-C22.2#250.0. Suitable for Wet Locations. |

Inground Luminaires**Options****Light distribution**

symmetric, medium beam [M]



symmetric, very narrow beam [VN]



symmetric, very narrow beam, 'sharp cut-off' [VNS]

Color temperature Nominal Watt

3000 K



8 W



4000 K

Inground Luminaires

Configurations

| Light distribution | Part ID | Light source | Delivered lumens | Rated input power | CRI | Weight (lb) |
|---|-------------------------------|--|------------------|-------------------|----------|----------------|
| symmetric, medium beam [M]  | 185-6228 185-6229 | LED-3/6W / 700 mA - 3000 K LED-3/6W / 700 mA - 4000 K | 591.9 632.8 | 7.5 W 7.5 W | 80 80 | 10.30 10.30 |
| symmetric, very narrow beam [VN]  | 185-6230 185-6231 | LED-3/6W / 700 mA - 3000 K LED-3/6W / 700 mA - 4000 K | 553.2 591.4 | 7.5 W 7.5 W | 80 80 | 10.30 10.30 |
| symmetric, very narrow beam, 'sharp cut-off' [VNS]  | 185-6232+185-9612 185-6233 | LED-3/6W / 700 mA - 3000 K LED-3/6W / 700 mA - 4000 K | 595.6 636.7 | 7.5 W 7.5 W | 80 80 | 10.30 10.30 |