

Description

IP66, Class I. IK09. Marine-grade, die-cast aluminium alloy. 5CE superior corrosion protection + primer including PCS hardware. Silicone CCG® Controlled Compression Gasket. PMMA main lens. The luminaire is factory sealed and does not need to be opened during installation. Integral EC converter. DALI. Factory installed LED circuit board. Removable LED boards for upgrading. CAD-optimised OLC® One LED Concept optics for superior illumination and glare control.

Pole mounted

Specifications**Material description**

Body	Marine-grade, die-cast aluminium alloy
Lens	PMMA
Colours	 RAL9004 Signal black  RAL9006 White aluminium  RAL9007 Grey aluminium
Gasket	Silicone CCG® Controlled Compression Gasket
Fasteners	PCS Polymer Coated Stainless Steel Hardware (unpainted)
Ingress protection	IP66
Impact resistance	IK09
Corrosion resistance	5CE+Primer
Windage	0.133 m ²

Electrical description

Power supply	230V / 50 Hz
Driver / Ballast	Integral EC electronic converter. DALI
Power factor	> 0.9
Surge protection	In-pole surge protection SP10 device supplied. Please refer to WE-EF installation instructions for details. Use suffix +A for Integral surge protection.

Additional information

Lifetime	Ta=40° L90B10 > 90000h
Warranty	The product is supplied with 10-year warranty. Please refer to the LED Warranty Statement located on www.we-ef.com for further details.

Options

Light distribution



rectangular, side throw [R65]



asymmetric, side throw [S65]

Colour temperature



3000 K



4000 K



2700 K



Nominal Watt

27 W

15 W

2 W

Configurations

Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI	Weight (kg)
asymmetric, side throw [S65] 	115-1293	LED-9/27W / 1050 mA - 3000 K	3269.5	29 W	80	5.60
	115-1294	LED-9/27W / 1050 mA - 4000 K	3421.5	29 W	80	5.60
	115-1369	LED-9/9W / 3000 K	1178.5	11 W	80	5.60
	115-1370	LED-9/9W / 4000 K	1292.6	11 W	80	5.60
	115-1371	LED-9/18W / 700 mA - 3000 K	2205	20 W	80	5.60
	115-1372	LED-9/18W / 700 mA - 4000 K	2357.1	20 W	80	5.60
	115-1605	LED-9/9W / 350 mA - 2700 K	1102.5	11 W	80	5.60
	115-1606	LED-9/18W / 700 mA - 2700 K	2052.9	20 W	80	5.60
	115-1617	LED-9/27W / 1050 mA - 2700 K	3117.4	29 W	80	5.60
	rectangular, side throw [R65] 	115-1289	LED-9/27W / 1050 mA - 3000 K	3354	29 W	80
115-1290		LED-9/27W / 1050 mA - 4000 K	3510	29 W	80	5.60
115-1365		LED-9/9W / 3000 K	1209	11 W	80	5.60
115-1366		LED-9/9W / 4000 K	1326	11 W	80	5.60
115-1367		LED-9/18W / 700 mA - 3000 K	2262	20 W	80	5.60
115-1368		LED-9/18W / 700 mA - 4000 K	2418	20 W	80	5.60
115-1607		LED-9/9W / 350 mA - 2700 K	1131	11 W	80	5.60
115-1608		LED-9/18W / 700 mA - 2700 K	2106	20 W	80	5.60
115-1616		LED-9/27W / 1050 mA - 2700 K	3198	29 W	80	5.60

Control**Eco Step Dim® Basic**

Description	Part ID
Eco Step Dim® Basic LED	430-0001


Eco Step Dim® Advanced

Description	Part ID
Eco Step Dim® Advanced LED	430-0002

Mounting Accessories

Wall and pole brackets RZ

Description	Part ID	C1	D1	D2	D × L1	M1	Weight (kg)
RZ0-400 Wall bracket, single	115-1324	277	231	195	76 x 80	12	3.50



RZ2-400 Pole bracket, double	115-1323	258			76 x 100		4.90
------------------------------	----------	-----	--	--	----------	--	------

