


Street and Area Lighting







Street and Area Lighting

Description

IP66. Post top luminaire with shielded light source and canopy highlight feature.

Street and Area Lighting

Specifications Material description

I	
Body	Marine-grade, die-cast aluminium alloy
Lens	PMMA
Colors	RAL9004 Black
	RAL9007 Grey Metallic
	RAL9016 White
	RAL8019 Dark Bronze
Gasket	Silicone CCG [®] Controlled Compression Gasket
Fasteners	PCS Polymer Coated Stainless Steel Hardware
Ingress protection	IP66
Impact resistance	IK08
Corrosion resistance	5CE
Windage	0.162 m ²
Electrical descripti	on

ectrical description

Power supply	220-240V / 50-60 Hz
Driver / Ballast	Integral EC electronic converter
Power factor	> 0.9

Additional information

Lifetime

Ta=25°/40° L90B10 > 90000h



Street and Area Lighting

Options Light distribution Color temperature Nominal Watt



Street and Area Lighting

Configurations

Light distribution	Part ID	Light source	Delivered	Rated input	CRI	Weight (lb)
			lumens	power		

Street and Area Lighting

Mounting Accessories

Wall and pole brackets RZ

Description	Part ID	C1	D1	D2	D × L1	M1	Weight (lb)
RZ0-400 Wall bracket, single	115-1324	10.90"	9.1"	7.67"	3" x 3"	0.47"	7.72 lbs
	D_2 O O D_1 M_1	C1-		– D x L1			
RZ2-400 Pole bracket, double	115-1323	10.16"			3" x 3"		10.8 lbs
	C1-		D ×	L1			

WE-EF LIGHTING USA, LLC

410-D Keystone Drive, 15086 Warrendale, PA 15086 - Phone: +1 724 742 0030 customersupport.usa@we-ef.com - https://we-ef.com/us Subject to technical changes and errors. - Generated on 07/02/2025 we-ef