

### Description

IP65. Class I. IK07. Marine-grade, die-cast aluminum alloy. 5CE superior corrosion protection including PCS hardware. Silicone CCG® Controlled Compression Gasket. Safety glass lens, hinged. CAD-optimized optics for superior illumination and glare control. Integral driver in thermally separated compartment. OLC® One LED Concept. Factory-installed LED circuit board. 0-10V Dimming comes standard with luminaire. Frame with safety catch. Gimbal mounted, 0-30° tiltable and 355° rotatable.

Suitable for installation over recessed junction box. A maximum of one internal optical accessory.

Specify product with 7 Digit product code - Finish Color. Accessories, such as mounting, optical, and electrical, must be specified separately.

Example: XXX-XXXX-9004 (Black)  
+ XXX-XXXX (Accessory 1)





# DAC240-GB LED

## Ceiling Luminaires

### Specifications

#### Material description

---

Body	Marine-grade die-cast aluminium alloy
Lens	Safety glass lens, hinged
Colors	 RAL9004 Black  RAL9007 Grey Metallic  RAL9016 White  RAL8019 Dark Bronze
Gasket	Silicone rubber gasket
Fasteners	PCS Polymer Coated Stainless Steel Hardware
Ingress protection	IP65
Impact resistance	IK07
Corrosion resistance	5CE

---

#### Electrical description

---

Power supply	Integral [ECG] electronic driver 120V-277V. 0-10V dimmable, to be specified with order.
Driver / Ballast	Integral EC electronic converter in thermally-separated compartment

---

#### Additional information

---

Lifetime	Ta=25°/40° L90B10 > 90000h
Listings	ETL, UL-1598, CSA-C22.2#250.0. Suitable for Wet Locations.

---

#### WE-EF LIGHTING USA, LLC

410-D Keystone Drive, 15086 Warrendale, PA 15086 - Phone: +1 724 742 0030  
customersupport.usa@we-ef.com - <https://we-ef.com/us>  
Subject to technical changes and errors. - Generated on 11/23/2024

# DAC240-GB LED

## Ceiling Luminaires

**we-ef**

### Options

#### Light distribution



symmetric, wide beam [W]



symmetric, medium beam [M]



symmetric, very narrow beam [VN]



symmetric, very narrow beam, 'sharp cut-off' [VNS]



wallwash [A20]



linear spread, medium beam [M]

#### Color temperature



3000 K



4000 K

#### Nominal Watt

21 W







#### WE-EF LIGHTING USA, LLC

410-D Keystone Drive, 15086 Warrendale, PA 15086 - Phone: +1 724 742 0030

customersupport.usa@we-ef.com - <https://we-ef.com/us>

Subject to technical changes and errors. - Generated on 11/23/2024

### Configurations

Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI	Weight (lb)
linear spread, medium beam [M] 	134-1598+185-2632	LED-12/18W / 500 mA - 3000 K	2041.9	21 W	80	18.70
	134-1599+185-2632	LED-12/18W / 500 mA - 4000 K	2184.3	21 W	80	18.70
symmetric, medium beam [M] 	134-1598	LED-12/18W / 500 mA - 3000 K	2241.6	21 W	80	18.70
	134-1599	LED-12/18W / 500 mA - 4000 K	2398	21 W	80	18.70
symmetric, very narrow beam [VN] 	134-1602	LED-12/18W / 500 mA - 3000 K	2137.9	21 W	80	18.70
	134-1603	LED-12/18W / 500 mA - 4000 K	2287	21 W	80	18.70
symmetric, very narrow beam, 'sharp cut-off' [VNS] 	134-1605	LED-12/18W / 500 mA - 3000 K	2388.2	21 W	80	18.70
	134-1606	LED-12/18W / 500 mA - 4000 K	2554.9	21 W	80	18.70
symmetric, wide beam [W] 	134-1596	LED-12/18W / 500 mA - 3000 K	1997.5	21 W	80	18.70
	134-1597	LED-12/18W / 500 mA - 4000 K	2136.8	21 W	80	18.70
wallwash [A20] 	134-1600	LED-12/18W / 500 mA - 3000 K	1798.6	21 W	80	18.70
	134-1601	LED-12/18W / 500 mA - 4000 K	1924	21 W	80	18.70

#### WE-EF LIGHTING USA, LLC

410-D Keystone Drive, 15086 Warrendale, PA 15086 - Phone: +1 724 742 0030

customersupport.usa@we-ef.com - <https://we-ef.com/us>

Subject to technical changes and errors. - Generated on 11/23/2024

# DAC240-GB LED

## Ceiling Luminaires


### Optical Accessories

#### Honeycomb louvre

---

Description	Part ID	C1
IW-DAC/DOC240-GB LED	134-1449	3.94

---



C1

---

#### WE-EF LIGHTING USA, LLC

410-D Keystone Drive, 15086 Warrendale, PA 15086 - Phone: +1 724 742 0030  
customersupport.usa@we-ef.com - <https://we-ef.com/us>

Subject to technical changes and errors. - Generated on 11/23/2024