



Description

IP44. Class I. IK10. Marine-grade, all aluminum construction. Anodized aluminum reflector. 5CE superior corrosion protection including PCS hardware. Silicone CCG® Controlled Compression Gaskets. Prismatic polycarbonate lenses. Service door with fused cable connecting box. Factory-installed LED circuit board.

3-Sided Light Distribution [3 x 120° offset].

Specify product with 7 Digit product code - Finish Color. Accessories, such as mounting, optical, and electrical, must be specified separately.

Example: XXX-XXXX-9004 (Black)

+ XXX-XXXX (Accessory 1)



Light Columns

Specifications Material description

Body Marine-grade, all-aluminium construction

Colors

RAL9004 Black

RAL9007 Grey Metallic

RAL9016 White

RAL8019 Dark Bronze

Gasket Silicone rubber gasket

Ingress protection IP44
Impact resistance IK10
Corrosion resistance 5CE

Electrical description

Power supply Integral [ECG] electronic driver 120V-277V. 0-10V dimmable, to be specified with order.

Driver / Ballast Integral EC electronic converter

Power factor > 0.9

Surge protection In-line bracket 10kV Surge Protector

Additional information

Lifetime $Ta=25^{\circ}/40^{\circ} L70B50 > 50000h$

BUG Rating Please see individual Spec Sheets for classification of Backlight, Uplight and Glare.

Listings ETL, UL-1598, CSA-C22.2#250.0. Suitable for Wet Locations.



Light Columns

Options Light distribution



three sided light output

Color temperature

3000 K

4000 K

Nominal Watt

0 W



Light Columns

Configurations

Light distribution	Part ID	Light source	Delivered lumens	Rated input power	CRI	Weight (lb)
three sided light output +	116-0208	LED-FT-37W (3000K)	2546.5	42 W	80	72.00
	116-0209	LED-FT-37W (4000K)	2656.2	42 W	80	72.00