

**Description**

IP44. Class I. IK10. Marine-grade, all aluminum construction. Anodized aluminum reflector. 5CE superior corrosion protection including PCS hardware. Silicone CCG® Controlled Compression Gaskets. Prismatic polycarbonate lenses. Service door with fused cable connecting box. Factory-installed LED circuit board.





3-Sided Light Distribution [3 x 120° offset].

Specify product with 7 Digit product code - Finish Color. Accessories, such as mounting, optical, and electrical, must be specified separately.

Example: XXX-XXXX-9004 (Black)  
+ XXX-XXXX (Accessory 1)

**Specifications****Material description**

Body	Marine-grade, all-aluminium construction
------	--

Colors	 RAL9004 Black
	 RAL9007 Grey Metallic
	 RAL9016 White
	 RAL8019 Dark Bronze

Gasket	Silicone rubber gasket
--------	------------------------

Ingress protection	IP44
--------------------	------

Impact resistance	IK10
-------------------	------

Corrosion resistance	5CE
----------------------	-----

**Electrical description**

Power supply	Integral [ECG] electronic driver 120V-277V. 0-10V dimmable, to be specified with order.
--------------	---

Driver / Ballast	Integral EC electronic converter
------------------	----------------------------------

Power factor	> 0.9
--------------	-------

Surge protection	In-line bracket 10kV Surge Protector
------------------	--------------------------------------

**Additional information**

Lifetime	Ta=25°/40° L70B50 > 50000h
----------	----------------------------

BUG Rating	Please see individual Spec Sheets for classification of Backlight, Uplight and Glare.
------------	---

Listings	ETL, UL-1598, CSA-C22.2#250.0. Suitable for Wet Locations.
----------	--

# LSP444 LED-FT

## Light Columns



### Options

#### Light distribution



three sided light output

#### Color temperature



3000 K



4000 K

#### Nominal Watt

0 W

### WE-EF LIGHTING USA, LLC


410-D Keystone Drive, 15086 Warrendale, PA 15086 - Phone: +1 724 742 0030  
customersupport.usa@we-ef.com - <https://we-ef.com/us>  
Subject to technical changes and errors. - Generated on 07/18/2025

LSP444 LED-FT

Light Columns



Configurations

Light distribution	Part ID	Light source	Delivered lumens	Rated input power	CRI	Weight (lb)
three sided light output 	116-0208	LED-FT-37W (3000K)	2546.5	42 W	80	72.00
	116-0209	LED-FT-37W (4000K)	2656.2	42 W	80	72.00