

### Description

Trilight column. IP44. IK10. Marine-grade, all-aluminium construction. 5CE superior corrosion protection including PCS hardware. Silicone rubber gaskets. Prismatic polycarbonate lenses.

Integral EC electronic converter. CAD-optimized lens for superior illumination and glare control.

Service door with fused cable connecting box.





Planted root available on request.

## Light columns

### Specifications

#### Material description

---

Body	Marine-grade, all-aluminium construction
Lens	Prismatic polycarbonate lenses
Colours	 RAL9004 Signal black  RAL9007 Grey aluminium  RAL7016 Anthracite grey  RAL9016 Traffic white
Gasket	Silicone rubber gasket
Fasteners	PCS hardware
Ingress protection	IP44
Impact resistance	IK10
Corrosion resistance	5CE

---

#### Electrical description

---

Power supply	220-240V / 50-60 Hz
Driver / Ballast	Integral EC electronic converter
Power factor	> 0.9

---

#### Additional information

---

Lifetime	Ta=25° L70B50 > 50000h
----------	------------------------

---

# LSP444 LED-FT

Light columns

**we-ef**

## Options

### Light distribution



three sided light output

### Colour temperature



3000 K




4000 K

### Nominal Watt

0 W

### Configurations

Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI	Weight (kg)
three sided light output 	116-0208	LED-FT-37W / 1050 mA - 3000 K	2546.5	42 W	80	32.60
	116-0209	LED-FT-37W / 1050 mA - 4000 K	2656.2	42 W	80	32.60

**Mounting Accessories**

**Planted root**

Description	Part ID	D1	D2	D3	D4	H1	H2	M1	T1	T2	Weight (kg)
Planted root ESD6	300-0456-AP	350	310	106	140	600	500	16	200	50 x 150	10.40

