



#### **Description**

IP44. Class I. IK10. Marine-grade, all aluminum construction. Anodized aluminum reflector. 5CE superior corrosion protection including PCS hardware. Silicone CCG® Controlled Compression Gaskets. Prismatic polycarbonate lenses. Service door with fused cable connecting box. Factory-installed LED circuit board.

3-Sided Light Distribution [3 x 120° offset].

Specify product with 7 Digit product code - Finish Color. Accessories, such as mounting, optical, and electrical, must be specified separately.

Example: XXX-XXXX-9004 (Black)

+ XXX-XXXX (Accessory 1)



#### **Light Columns**

## **Specifications Material description**

Body Marine-grade, all-aluminium construction

Lens Prismatic polycarbonate lenses, 3 x 120° offset

Colors RAL9004 Black

RAL9007 Grey Metallic

RAL9016 White

RAL8019 Dark Bronze

Gasket Silicone rubber gasket

Fasteners PCS Polymer Coated Stainless Steel hardware

Ingress protection IP44
Impact resistance IK10
Corrosion resistance 5CE

#### **Electrical description**

Power supply Integral [ECG] electronic driver 120V-277V. 0-10V dimmable, to be specified with order.

Driver / Ballast Integral EC electronic converter

Power factor > 0.9

Surge protection In-line bracket 10kV Surge Protector

#### **Additional information**

Lifetime  $Ta=25^{\circ}/40^{\circ} L70B50 > 50000h$ 

BUG Rating Please see individual Spec Sheets for classification of Backlight, Uplight and Glare.

Listings ETL, UL-1598, CSA-C22.2#250.0. Suitable for Wet Locations.



## **Light Columns**

# Options Light distribution



three sided light output

## Color temperature

Nominal Watt

3000 K

4000 K

## **Light Columns**

## **Configurations**

Light distribution	Part ID	Light source	Delivered lumens	Rated input power	CRI	Weight (lb)
three sided light output +	116-0212	LED-FT-37W (3000K)	2546.5	42 W	80	37.50
	116-0213	LED-FT-37W (4000K)	2656.2	42 W	80	37.50