

Description





Trilight column. IP44. IK10. Marine-grade, all-aluminium construction. 5CE superior corrosion protection including PCS hardware. Silicone rubber gaskets. Prismatic polycarbonate lenses.

Integral HPF control gear. LPF versions available on request. Service door with fused cable connecting box. Planted root available on request.

Light columns

Specifications

Material description

Body	Marine-grade, all-aluminium construction
Lens	Prismatic polycarbonate lenses
Colours	 RAL9004 Signal black  RAL9007 Grey aluminium  RAL7016 Anthracite grey  RAL9016 Traffic white
Gasket	Silicone rubber gasket
Fasteners	PCS hardware
Ingress protection	IP44
Impact resistance	IK10
Corrosion resistance	5CE

Electrical description

Power supply	220-240V / 50-60 Hz
Driver / Ballast	Integral EC electronic converter
Power factor	> 0.9

Additional information

Lifetime	Ta=25° L70B50 > 50000h
----------	------------------------

LSP434 LED-FT

Light columns

we-ef

Options

Light distribution



three sided light output

Colour temperature



3000 K



4000 K


Nominal Watt

0 W

LSP434 LED-FT

Light columns

Configurations

Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI	Weight (kg)
three sided light output 	116-0212	LED-FT-37W / 1050 mA - 3000 K	2546.5	42 W	80	16.90
	116-0213	LED-FT-37W / 1050 mA - 4000 K	2656.2	42 W	80	16.90