
Inground luminaires







Description

IP67, Class I. IK07. Stainless steel inground section. Diecast hood made from marine-grade aluminium alloy. Construction helps to prevent accumulation of insects, leaves and debris on lens and restricts glare to passersby. 5CE superior corrosion protection including PCS hardware. Safety glass lens. Silicone rubber gasket. Factory-sealed termination chamber with cable gland and 1.5 m of flexible PVC-free cable.

Integral EC electronic converter. Advanced thermal management protects LEDs while optimising lumens output. Removable LED boards for upgrading. CAD-optimised optics for superior illumination and glare control. Luminaire installation blockout and sealable junction box included in supply.



Inground luminaires

Specifications Material description

Body Stainless steel inground section. Die-cast dome made from marine-grade aluminium alloy

Colours

RAL9004 Signal black

RAL9007 Grey aluminium

RAL7016 Anthracite grey

RAL9016 Traffic white

Ingress protection IP67
Impact resistance IK07
Corrosion resistance 5CE

Electrical description

Additional information

Lifetime Ta=25° L90B10 > 90000h

we-ef

Inground luminaires

Options

Light distribution Colour temperature Nominal Watt



Inground luminaires

Configurations

Light distribution	Part ID	Light source	Rated	Rated input	t CRI	Weight (kg)
			lumens	power		




Inground luminaires

Mounting Accessories

Installation blockout

Description	Part ID	D1	D2	H1	Weight (kg)	D	Н
Blockout, Plastic	185-0323	300	325	420	2.50	300/325	420



Installation cover

Description
nstallation cover BE





Inground luminaires

Control

1-10 V analogue dimming interface

Description	Part ID
1-10 V analogue dimming interface	430-0011