

### Description

DOC110 LED for remodel projects. For new construction, see DOC110 LED [New Construction] version.

IP66, Class I. IK07. Marine-grade, die-cast aluminum alloy. 5CE superior corrosion protection including PCS hardware. Silicone CCG® Controlled Compression Gasket. Safety glass lens. Separate IP66 driver housing. CAD-optimized optics for superior illumination and glare control. OLC® One LED Concept. Factory installed LED circuit board. 0-10V Dimming comes standard with luminaire.

A pre-installation blockout, proud or flush, is available and recommended for mounting in concrete ceilings; to be ordered separately.

Specify product with 7 Digit product code - Finish Color. Accessories, such as mounting, optical, and electrical, must be specified separately.

Example: XXX-XXXX - 9004 (Black)

+ XXX-XXXX (Accessory 1)

## Ceiling Luminaires

### Specifications

#### Material description

Body	Marine-grade, die-cast aluminium alloy
Lens	Safety glass lens
Colors	<div><div></div> RAL9004 Black</div> <div><div></div> RAL9007 Grey Metallic</div> <div><div></div> RAL9016 White</div> <div><div></div> RAL8019 Dark Bronze</div>
Gasket	Silicone CCG® Controlled Compression Gasket
Fasteners	PCS Polymer Coated Stainless Steel Hardware
Ingress protection	IP66
Impact resistance	IK07
Corrosion resistance	5CE

#### Electrical description

Power supply	Integral 120-277V/0-10V dimming driver
Driver / Ballast	Integral EC electronic converter in thermally-separated compartment

#### Additional information

Lifetime	Ta=25°/40° L90B10 > 90000h
Listings	ETL, UL-1598, CSA-C22.2#250.0. Suitable for Wet Locations.








# DOC110 LED [For Remodel]






## Ceiling Luminaires

### Options

#### Light distribution

	symmetric, wide beam [W]
	symmetric, medium beam [M]
	symmetric, very narrow beam [VN]
	symmetric, very narrow beam, 'sharp cut-off' [VNS]
	wallwash [A20]
	linear spread, very narrow beam
	linear spread, very narrow beam, 'sharp cut-off'

#### Color temperature      Nominal Watt

	3000 K	15 W 155 W
	4000 K	
	2700 K	







#### WE-EF LIGHTING USA, LLC

410-D Keystone Drive, 15086 Warrendale, PA 15086 - Phone: +1 724 742 0030  
customersupport.usa@we-ef.com - <https://we-ef.com/us>  
Subject to technical changes and errors. - Generated on 08/15/2025

## Ceiling Luminaires

**we-ef**

## Configurations

Light distribution	Part ID	Light source	Delivered lumens	Rated input power	CRI	Weight (lb)
linear spread, very narrow beam, 'sharp cut-off'	134-1633+134-1637	LED-6/12W / 700 mA - 3000 K	1526.2	14.5 W	80	2.86
	134-1634+134-1637	LED-6/12W / 700 mA - 4000 K	1631.5	14.5 W	80	2.86
						
linear spread, very narrow beam	134-1631+134-1637	LED-6/12W / 700 mA - 3000 K	1386.3	14.5 W	80	2.86
	134-1632+134-1637	LED-6/12W / 700 mA - 4000 K	1481.9	14.5 W	80	2.86
						
symmetric, medium beam [M]	134-1627	LED-6/12W / 700 mA - 3000 K	1511.8	14.5 W	80	2.86
	134-1628	LED-6/12W / 700 mA - 4000 K	1616.1	14.5 W	80	2.86
	134-1908	LED-6/12W / 700 mA - 2700 K	1407.5	14.5 W	80	2.86
						
symmetric, very narrow beam [VN]	134-1631	LED-6/12W / 700 mA - 3000 K	1496.5	14.5 W	80	2.86
	134-1632	LED-6/12W / 700 mA - 4000 K	1599.7	14.5 W	80	2.86
	134-1909	LED-6/12W / 700 mA - 2700 K	1393.3	14.5 W	80	2.86
						
symmetric, very narrow beam, 'sharp cut-off' [VNS]	134-1633	LED-6/12W / 700 mA - 3000 K	1610.7	14.5 W	80	2.86
	134-1634	LED-6/12W / 700 mA - 4000 K	1721.8	14.5 W	80	2.86
	134-1910	LED-6/12W / 700 mA - 2700 K	1499.6	14.5 W	80	2.86
						
symmetric, wide beam [W]	134-1625	LED-6/12W / 700 mA - 3000 K	1347.1	14.5 W	80	2.86
	134-1626	LED-6/12W / 700 mA - 4000 K	1440	14.5 W	80	2.86
	134-1907	LED-6/12W / 700 mA - 2700 K	1254.2	14.5 W	80	2.86
						
wallwash [A20]	134-1627+134-1683	LED-6/12W / 700 mA - 3000 K	1142.4	14.5 W	80	2.86
	134-1628+134-1683	LED-6/12W / 700 mA - 4000 K	1221.2	14.5 W	80	2.86
	134-1908+134-1683	LED-6/12W / 700 mA - 2700 K	1063.6	14.5 W	80	2.86

**WE-EF LIGHTING USA, LLC**

410-D Keystone Drive, 15086 Warrendale, PA 15086 - Phone: +1 724 742 0030

customersupport.usa@we-ef.com - <https://we-ef.com/us>

Subject to technical changes and errors. - Generated on 08/15/2025

DOC110 LED [For Remodel]

Ceiling Luminaires



Light distribution	Part ID	Light source	Delivered lumens	Rated input power	CRI	Weight (lb)

Optical Accessories

Linear spread lens

Description	Part ID	C1
IO-180-DOC110-LED	134-1637	3.86




DOC110 LED [For Remodel]

Ceiling Luminaires



Wallwash lens

Description	Part ID	C1
IO-20-DOC110-LED	134-1683	3.85



Mounting Accessories

Installation blackout

Description	Part ID	A	B	C1	D1
Installation blackout BD011-I	134-1639	13.11	9.13	6.77	4.60

