







#### **Description**

IP55, Class I. IK10. Marine-grade, all-aluminium construction. 5CE superior corrosion protection + primer including PCS hardware. Polycarbonate prismatic lens. Silicone rubber gaskets. Impregnated hardwood post. Integral EC electronic converter in thermally-separated compartment. Advanced thermal management protects LEDs while optimising lumens output.



### **Bollards and pathway luminaires**

# **Specifications**

### **Material description**

Body Marine-grade, all-aluminium construction

Lens Polycarbonate prismatic lens

Colours RAL9004 Signal black

RAL9006 White aluminium
RAL9007 Grey aluminium

Gasket Silicone rubber gaskets

Fasteners PCS hardware

Ingress protection IP55
Impact resistance IK10

Corrosion resistance 5CE+Primer

### **Electrical description**

Driver / Ballast Integral EC electronic converter in thermally-separated compartment

#### Additional information



**Bollards and pathway luminaires** 

**Options** 

Light distribution Colour temperature Nominal Watt



# **Bollards and pathway luminaires**

# **Configurations**

Light distribution	Part ID	Light source	Rated	Rated input	CRI	Weight (kg)
			lumens	power		



# **Bollards and pathway luminaires**

# **Mounting Accessories**

### **Planted root**

Description	Part ID	D1	D2	D3	D4	H1	H2	M1	T1	T2	Weight (kg)
Planted root ESV4	300-0464-AP	220	190	60	102	400	350	8	200	50 x 100	5.50

