

Description

IP67, Class I. IK09. Marine-grade, all aluminium construction. 5CE superior corrosion protection + primer including PCS hardware. PMMA cover. Silicone rubber gasket. Linear PMMA LED lens. 1.2 m connecting cable, UV stabilized, PVC free. Luminaire is factory sealed and does not need to be opened during installation and can be tilted up to 180°. Integral LED driver with DALI interface.

Separate LED driver on request.

Specifications**Material description**

| | |
|----------------------|---|
| Body | Marine-grade, all-aluminium construction |
| Lens | PMMA |
| Colours |  RAL9004 Signal black  RAL9006 White aluminium  RAL9007 Grey aluminium |
| Gasket | Silicone rubber gasket |
| Fasteners | PCS Polymer Coated Stainless Steel Hardware (unpainted) |
| Ingress protection | IP67 |
| Impact resistance | IK09 |
| Corrosion resistance | 5CE+Primer |

Electrical description

| | |
|------------------|---|
| Power supply | 230V / 50 Hz |
| Driver / Ballast | Integral LED driver with DALI Interface |

Additional information

| | |
|----------|--|
| Lifetime | T _a =40° L90B10 > 90000h |
| Warranty | The product is supplied with 10-year warranty. Please refer to the LED Warranty Statement located on www.we-ef.com for further details. |

Options**Light distribution**

asymmetric linear, wallwash [LA10]

Colour temperature

19 W



3000 K




4000 K



2700 K

Configurations

| Light distribution | Part ID | Light source | Rated lumens | Rated input power | CRI | Weight (kg) |
|--|----------|------------------------------|--------------|-------------------|-----|-------------|
| asymmetric linear, wallwash [LA10] | 187-0014 | LED-32/20W / 225 mA - 3000 K | 2049.8 | 23.5 W | 80 | 2.45 |
|  | 187-0329 | LED-32/20W / 225 mA - 4000 K | 2049.8 | 23.5 W | 80 | 2.45 |
| | 187-0549 | LED-32/20W / 225 mA - 2700 K | 2049.8 | 23.5 W | 80 | 2.45 |