

#### **Description**

IP67. Class I. IK09. Marine-grade, all aluminum construction. 5CE superior corrosion protection including PCS hardware. Silicone CCG® Controlled Compression Gasket. Linear PMMA LED lens, PMMA cover. 4 ft connecting cable, UV stabilized, PVC free. Integral LED driver; separate LED driver available instead, on request at time of order. 0-10V Dimming comes standard with luminaire. Luminaire is factory-sealed and does not need to be opened during installation and can be tilted up to 180°.

Specify product with 7 Digit product code - Finish Color. Accessories, such as mounting, optical, and electrical, must be specified separately.

Example: XXX-XXXX-9004 (Black) + XXX-XXXX (Accessory 1)



#### **Surface Mounted Wall Luminaires**

## **Specifications**

## **Material description**

Body Marine-grade, all-aluminium construction

Lens PMMA

Colors RAL9004 Black

RAL9007 Grey Metallic

RAL9016 White

RAL8019 Dark Bronze

Fasteners PCS Polymer Coated Stainless Steel Hardware

Ingress protection IP67
Impact resistance IK09
Corrosion resistance 5CE

## **Electrical description**

Power supply Integral [ECG] electronic driver 120V-277V. 0-10V dimmable, to be specified with order.

Driver / Ballast LED driver with DALI Interface

#### **Additional information**

Lifetime  $Ta=25^{\circ}/40^{\circ} L90B10 > 90000h$ 

Listings ETL, UL-1598, CSA-C22.2#250.0. Suitable for Wet Locations. Meets ANSI C136.31 - 3G Vibration

Rating for Bridge and Overpass Applications.



### **Surface Mounted Wall Luminaires**


# Options Light distribution



asymmetric linear, wallwash [LA10]

# **Color temperature** Nominal Watt

19 W





### **Surface Mounted Wall Luminaires**

# **Configurations**

Light distribution	Part ID	Light source	Delivered lumens	Rated input power	CRI	Weight (lb)
asymmetric linear, wallwash [LA10]	187-0014	LED-32/20W / 225 mA - 3000 K	2049.8	23.5 W	80	5.40
	187-0329	LED-32/20W / 225 mA - 4000 K	2049.8	23.5 W	80	5.40
	187-0549	LED-32/20W / 225 mA - 2700 K	2049.8	23.5 W	80	5.40