

- -----

Wall luminaires surface mounted





____468_____

Description

IP67, Class I. IK09. Marine-grade, all aluminium construction. 5CE superior corrosion protection including PCS hardware. Silicone rubber gasket. PMMA. Linear PMMA LED lens. 1.2 m connecting cable, UV stabilized, PVC free. Luminaire is factory sealed and does not need to be opened during installation and can be tilted up to 180°. Integral LED driver with DALI interface.

Separate LED driver on request.

VLR130 [LA10]

Wall luminaires surface mounted

we-ef

Specifications Material description

Body	Marine-grade, all-aluminium construction					
Lens	PMMA					
Colours	RAL9004 Signal black					
	RAL9006 White aluminium					
	RAL9007 Grey aluminium					
	RAL7016 Anthracite grey					
	RAL9016 Traffic white					
Gasket	Silicone rubber gasket					
Fasteners	PCS Polymer Coated Stainless Steel Hardware					
Ingress protection	IP67					
Impact resistance	IK09					
Corrosion resistance	5CE					

Power supply	220-240V / 50-60 Hz
Driver / Ballast	Integral LED driver with DALI Interface

Additional information

Lifetime	Ta=25° L90B10 > 90000h
Energy efficiency class	D (Light source)

VLR130 [LA10]

Wall luminaires surface mounted



Options Light distribution

asymmetric linear, wallwash [LA10]



VLR130 [LA10]

Wall luminaires surface mounted

we-ef

Configurations

Light distribution	Part ID	Light source	Rated	Rated input	CRI	Weight (kg)
			lumens	power		
asymmetric linear, wallwash [LA10]	187-0015	LED-48/30W / 225 mA - 3000 K	3074.8	33.5 W	80	3.25
	187-0330	LED-48/30W / 225 mA - 4000 K	3074.8	33.5 W	80	3.25
	187-0550	LED-48/30W / 225 mA - 2700 K	3074.8	33.5 W	80	3.25

WE-EF LEUCHTEN GmbH Töpinger Straße 16, 29646 Bispingen, Germany - Phone: +49 5194 909-0 info@we-ef.com - https://we-ef.com Subject to technical changes and errors. - Generated on 18/07/2025