

---

**Description**

IP67, Class I. IK09. Marine-grade, all aluminium construction. 5CE superior corrosion protection + primer including PCS hardware. PMMA cover. Silicone rubber gasket. Linear PMMA LED lens. 1.2 m connecting cable, UV stabilized, PVC free. Luminaire is factory sealed and does not need to be opened during installation and can be tilted up to 180°. Integral LED driver with DALI interface.




Separate LED driver on request.

**Wall luminaires surface mounted**

---

**Specifications****Material description**

---

Body	Marine-grade, all-aluminium construction
Lens	PMMA
Colours	 RAL9004 Signal black  RAL9006 White aluminium  RAL9007 Grey aluminium
Gasket	Silicone rubber gasket
Fasteners	PCS Polymer Coated Stainless Steel Hardware (unpainted)
Ingress protection	IP67
Impact resistance	IK09
Corrosion resistance	5CE+Primer

---

**Electrical description**

---

Power supply	230V / 50 Hz
Driver / Ballast	Integral LED driver with DALI Interface

---

**Additional information**

---

Lifetime	Ta=40° L90B10 > 90000h
Warranty	The product is supplied with 10-year warranty. Please refer to the LED Warranty Statement located on <a href="http://www.we-ef.com">www.we-ef.com</a> for further details.

---

Options

Light distribution



asymmetric linear, wallwash [LA10]

Colour temperature



3000 K



4000 K




2700 K

Nominal Watt

35 W

## Configurations

Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI	Weight (kg)
asymmetric linear, wallwash [LA10] 	187-0016	LED-64/40W / 225 mA - 3000 K	4099.7	44 W	80	4.00
	187-0237	LED-64/40W / 225 mA - 2700 K	4099.7	44 W	80	4.00
	187-0331	LED-64/40W / 225 mA - 4000 K	4099.7	44 W	80	4.00