



Inground Luminaires

Inground Luminaires**Description**

RGBW Color Changer.

IP69K. Class I. IK08. Marine-grade, all aluminum construction. Anodized aluminum extrusion. PCS hardware. Silicone CCG® Controlled Compression Gasket. Safety glass lens; max static load, 3.3 tons (6,600 lbs) (according to DIN EN 60598-2-13). Luminaire can be driven over at low speed, without accelerating or turning, by vehicles with air-filled tires, at a weight up to 5.5 tons (11,000 lbs) per wheel. Factory-sealed termination chamber complete with cable gland and 3 ft of flexible PVC-free, gel-impregnated anti-wicking cable. Linear PMMA LED lens. Integral driver in thermally separated compartment. Factory-installed LED circuit board. LED board can be easily removed for upgrading. DMX interface. Luminaire is factory-sealed and does not need to be opened during installation.

The installation blockout to be ordered separately; blockouts can house between 1-4 luminaires.

Specify product with 7 Digit product code - Finish Color. Accessories, such as mounting, optical, and electrical, must be specified separately.

Inground Luminaires

Example: XXX-XXXX-9004 (Black)

+ XXX-XXXX (Accessory 1)

Inground Luminaires**Specifications****Material description**


Body	Marine-grade all aluminium construction. Anodized aluminium extrusion.
Lens	Safety glass lens
Colors	
Gasket	Silicone CCG® Controlled Compression Gasket
Fasteners	PCS Polymer Coated Stainless Steel Hardware
Ingress protection	IP69K - HIGHEST PROTECTION RATING AVAILABLE
Impact resistance	IK08

Electrical description

Power supply	Integral [ECG] electronic driver 120V-277V. DMX Dimmable.
Driver / Ballast	Integral DMX electronic converter
Power factor	> 0.9

Additional information


Lifetime	Ta=25°/40° L90B10 > 90000h
Listings	ETL, UL-1598, CSA-C22.2#250.0. Suitable for Wet Locations.

Inground Luminaires**Options****Light distribution****Color temperature****Nominal Watt**

symmetric linear, wide beam [LW]

RGBW/4K

0 W



symmetric linear, medium beam [LM]



symmetric linear, narrow beam [LN]







symmetric linear, very narrow beam [LVN]




asymmetric linear, wallwash [LA10]

Inground Luminaires**Configurations**

Light distribution	Part ID	Light source	Delivered lumens	Rated input power	CRI	Weight (lb)
asymmetric linear, wallwash [LA10]	186-0265	LED-96/48W - RGBW/4K	3326.7	52 W	80	13.50
						
symmetric linear, medium beam [LM]	186-0256	LED-96/48W - RGBW/4K	3473.6	52 W	80	13.50
						
symmetric linear, narrow beam [LN]	186-0259	LED-96/48W - RGBW/4K	3410.2	52 W	80	13.50
						
symmetric linear, very narrow beam [LVN]	186-0262	LED-96/48W - RGBW/4K	3904.6	52 W	80	13.50
						
symmetric linear, wide beam [LW]	186-0253	LED-96/48W - RGBW/4K	3191	52 W	80	13.50
						


Inground Luminaires**Electrical Accessories****Sealable junction box**

Description	Part ID	C1	M1	M2
Sealable junction box SJB 130	185-1624	5.75	\varnothing 0.39	\varnothing 0.47 - 0.75




Inground Luminaires**Optical Accessories****Honeycomb louvre**

Description	Part ID	C1	H1
IW for ETV130	186-0295	35.35	1.18




Inground Luminaires**Mounting Accessories****Installation breakout, Type I**

Description	Part ID	A	C1	D1	D2	Weight (lb)
BEV130-I-1/927 (1 luminaire)	186-0310	38.38"	6.30	2.13	4.72	10.36 lbs




BEV130-I-2/927 (2 luminaires)	186-0311	74.96	6.30	2.13	4.72	19.84
-------------------------------	----------	-------	------	------	------	-------




Inground Luminaires

Description	Part ID	A	C1	D1	D2	Weight (lb)
BEV130-I-3/927 (3 luminaires)	186-0312	111.54	6.30	2.13	4.72	29.10 lbs



BEV130-I-4/927 (4 luminaires)	186-0313	148.11	6.30	2.13	4.72	38.58
-------------------------------	----------	--------	------	------	------	-------



Inground Luminaires**Control****DMX Booster Box**

Description	Part ID
DMX Booster Box	400-0474

**DMX Controller**

Description	Part ID	Additional information
DMX Controller	400-0469	IP20. DIN Rail system. Is designed for either live or stand-alone control. It features one DMX universe, a USB connection, 128k flash memory for storing stand-alone programs.

Inground Luminaires**DMX Controller (smart)**

Description	Part ID	Additional information
DMX Controller (smart)	400-0470	IP20. The Touch Panel is an untutive abd easy-to use keypad or one DMX universe. It can store up to 36 scences; alternatively, via



Inground Luminaires**DMX Plug and Socket**

Description	Part ID
DMX Plug and Socket	400-0479

**DMX Termination Plug**

Description	Part ID
DMX Termination Plug	400-0475



Inground Luminaires**DMX Combination Cable**

Description	Part ID
DMX Combination Cable	400-0480

