

### Description

RGBW Colour Changer. IP67, Class I. IK08. Marine-grade all aluminium construction. Anodized aluminium extrusion. PCS hardware. Silicone rubber gasket. Safety glass lens. Luminaire can be driven over at low speed, without accelerating or turning, by vehicles with air-filled tyres, at a weight up to 5 tonnes per wheel. Max. static load, 3 tonnes (according to DIN EN 60598-2-13). Factory-sealed termination chamber complete with cable gland and 0.5 m of flexible cable, including sealable junction box SJB. Linear PMMA LED lens. Factory installed LED circuit board. LED boards can be easily removed for upgrading. Luminaire is factory sealed and does not need to be opened during installation. Integral electronic converter with DMX interface in thermally-separated compartment.

The optional installation blockout is recommended for mounting. To be ordered separately.

**IMPORTANT!** Inground blockouts must be installed with effective drainage, watch **<a href="https://vimeo.com/672613058">here.</a></strong>**

**Specifications****Material description**

Body	Marine-grade all aluminium construction. Anodized aluminium extrusion.
Lens	Safety glass lens
Colours	
Gasket	Silicone rubber gasket
Fasteners	PCS Polymer Coated Stainless Steel Hardware (unpainted)
Ingress protection	IP67
Impact resistance	IK08

**Electrical description**

Power supply	230V / 50 Hz
Driver / Ballast	Integral electronic converter with DMX interface in thermally-separated compartment
Power factor	> 0.9

**Additional information**

Lifetime	Ta=40° L90B10 > 90000h
Warranty	The product is supplied with 10-year warranty. Please refer to the LED Warranty Statement located on <a href="http://www.we-ef.com">www.we-ef.com</a> for further details. Warranty void if installed without proper drainage.

**Options****Light distribution****Colour temperature****Nominal Watt**

symmetric linear, wide beam [LB]

0 W



symmetric linear, medium beam [LM]


RGBW/4K



symmetric linear, narrow beam [LE]







symmetric linear, very narrow beam [LEE]




asymmetric linear, wallwash [LA10]

**Configurations**

Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI	Weight (kg)
asymmetric linear, wallwash [LA10]	186-0280	LED-128/64W - RGBW/4K	4435.7	67 W	20/80	7.50
						
symmetric linear, medium beam [LM]	186-0271	LED-128/64W - RGBW/4K	4631.5	67 W	20/80	7.50
						
symmetric linear, narrow beam [LE]	186-0274	LED-128/64W - RGBW/4K	4546.9	67 W	20/80	7.50
						
symmetric linear, very narrow beam [LEE]	186-0277	LED-128/64W - RGBW/4K	5206.2	67 W	20/80	7.50
						
symmetric linear, wide beam [LB]	186-0268	LED-128/64W - RGBW/4K	4254.6	67 W	20/80	7.50
						


**Electrical Accessories****Sealable junction box**

Description	Part ID	C1	M1	M2
Sealable junction box SJB130	185-1624	146	Ø 10	Ø 12 - 19




**Optical Accessories****Honeycomb louvre**

Description	Part ID	C1	H1
IW for ETV140	186-0296	1198	30




**Mounting Accessories****Installation blockout, Type I**

Description	Part ID	A	C1	D1	D2	Weight(kg)
BEV140-I-1/1227 (1 luminaire)	186-0314	1275	160	55	120	6.10




BEV140-I-2/1227 (2 luminaires)	186-0315	2504	160	55	120	11.70
--------------------------------	----------	------	-----	----	-----	-------



**Inground luminaires**

Description	Part ID	A	C1	D1	D2	Weight(kg)
BEV140-I-3/1227 (3 luminaires)	186-0316	3733	160	55	120	17.40



BEV140-I-4/1227 (4 luminaires)	186-0317	4962	160	55	120	23
--------------------------------	----------	------	-----	----	-----	----

