

### Description

RGBW/RGBA Colour Changer. IP66, Class I. Class II on request. IK07. Marine-grade, die-cast aluminium alloy. 5CE superior corrosion protection including PCS hardware. Silicone CCG® Controlled Compression Gasket. Safety glass lens. One cable gland. Second gland for through-wiring on request. Integral EC electronic converter, thermally separated. CAD-optimised optics for superior illumination and glare control. OLC® One LED Concept. Factory-installed LED circuit board with WE-EF Colour Boost Technology. With Colour Boost the targeted and selective control of individual channels or colours means that a higher power of the LEDs can be accessed than in total when all colours are simultaneously operated. The light output is thus maximized by targeted control of individual channels/colours.

DMX interface. For the M20 cable gland for network- and DMX-connection, WE-EF recommends a multi-core cable for DMX and power, "Power PUR-SR 3x1,5 + DMX".

**Projectors****Specifications****Material description**

Body	Marine-grade, die-cast aluminium alloy
Lens	Safety glass lens
Colours	 RAL9004 Signal black  RAL9006 White aluminium  RAL9007 Grey aluminium  RAL7016 Anthracite grey  RAL9016 Traffic white
Gasket	Silicone CCG® Controlled Compression Gasket
Fasteners	PCS Polymer Coated Stainless Steel Hardware
Ingress protection	IP66
Impact resistance	IK07
Corrosion resistance	5CE
Windage	0.116 m <sup>2</sup>

**Electrical description**

Power supply	220-240V / 50-60 Hz
Driver / Ballast	DMX
Power factor	> 0.9
Surge protection	1/2 kV (optional SP10)

**Additional information**











Lifetime	Ta=25° L90B10 > 90000h
Energy efficiency class	G (Light source)

## Options

### Light distribution


	Colour temperature	Nominal Watt
 symmetric, medium beam [M]	RGBW/4K	0 W
 symmetric, narrow beam [E]	RGBW/4K	0 W
 symmetric, wide beam [B]	RGBW/4K	0 W
 linear spread, narrow beam [E]	RGBW/4K	0 W
 wallwash	RGBW/4K	0 W
 symmetric, very narrow beam, sharp cut-off [EES]	RGBW/4K	0 W
 linear spread, very narrow beam, sharp cut-off [EES]	RGBW/4K	0 W

## Configurations

Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI	Weight (kg)
linear spread, narrow beam [E]	139-1891+139-1861 	LED-36/144W - RGBW/4K	9733.5	149 W	20/80	18.00
	139-2144+139-1861 	LED-36/144W - RGBA	8722.2	149 W	20	18.00
linear spread, very narrow beam, sharp cut-off [EES]	139-2428+139-1861 	LED-4x18/126W - RGBW/4K	7500.9	131 W	20/80	18.00
	139-2430+139-1861 	LED-4x18/126W - RGBA	7425.1	131 W	20	18.00
symmetric, medium beam [M]	139-1889 	LED-36/144W - RGBW/4K	10887.4	149 W	20/80	18.00
	139-2145 	LED-36/144W - RGBA	9756.2	149 W	20	18.00
symmetric, narrow beam [E]	139-1891 	LED-36/144W - RGBW/4K	10679.4	149 W	20/80	18.00
	139-2144 	LED-36/144W - RGBA	9569.8	149 W	20	18.00
symmetric, very narrow beam, sharp cut-off [EES]	139-2428 	LED-4x18/126W - RGBW/4K	7719.9	131 W	20/80	18.00
	139-2430 	LED-4x18/126W - RGBA	7641.9	131 W	20	18.00
symmetric, wide beam [B]	139-1965 	LED-36/144W - RGBW/4K	10133.6	149 W	20/80	18.00
	139-2143 	LED-36/144W - RGBA	9080.7	149 W	20	18.00
wallwash	139-1889+139-1860 	LED-36/144W - RGBW/4K	8829.3	149 W	20/80	18.00
	139-2145+139-1860 	LED-36/144W - RGBA	7911.9	149 W	20	18.00

**Optical Accessories****Flood lens**


Description	Part ID	C1
I0-360-FLC260-LED	139-1862	332



C1

**Honeycomb louvre**

Description	Part ID	C1	H1
IW-03-FLC260-LED - [E][EE][EES]	139-1863	324	




C1

**Projectors**


---

Description	Part ID	C1	H1
IW-FLC26_EES-CC LED	139-2434	232	209

**Linear spread lens**


---

Description	Part ID	C1
I0-180-FLC260-CC LED	139-1861	332




**Projectors****Wallwash lens**

Description	Part ID	C1
IO-20-FLC260-CC LED	139-1860	332


**Snoot**

Description	Part ID	A	C1
ET-FLC260-LED	139-1865	222	393





**Glare shield**

Description	Part ID	A	C1
ES-FLC260-LED	139-1864	222	393





**Mounting Accessories****Pole clamp TS**

Description	Part ID	D1	Weight (kg)	D
TS1-2/M12 Pole clamp, single (Ø 76-89)	147-0543	76-89	1.40	76-89



D1



TS1-2/M12 Pole clamp, single (Ø 114-133)	147-0544	114-133	1.70	114-133
--	----------	---------	------	---------





D1

**Projectors**

Description	Part ID	D1	Weight (kg)	D
TS2-2/M12 Pole clamp, double (Ø 76-89)	147-0545	76-89	1.40	76-89




TS2-2/M12 Pole clamp, double (Ø 114-133)	147-0546	114-133	1.60	114-133
--	----------	---------	------	---------




**Projectors****Floodlight mounting bracket TA**

Description	Part ID	C1	D × L1	Weight (kg)	D × S
TA1 Mounting bracket, single* (Ø 76 x 200)	147-0023	130	76 x 200	1.90	76 x 200



**Pole clamp PC**

Description	Part ID	D1	Weight (kg)
PC2 76-89/60 Pole clamp, double (Ø 76-89)	139-2703	76-89	1.00





**Projectors**

Description	Part ID	D1	Weight (kg)
PC1 76-89/60 Pole clamp, single (Ø 76-89)	139-2702	76-89	1.00



D1



PC2 102-114/60 Pole clamp, double (Ø 102-114)	139-2707	102-114	1.20
---	----------	---------	------



D1



**Projectors**

Description	Part ID	D1	Weight (kg)
PC1 102-114/60 Pole clamp, single (Ø 102-114)	139-2706	102-114	1.20



D1



PC2 114-133/60 Pole clamp, double (Ø 114-133)	139-2709	114-133	1.40
--	----------	---------	------





D1

**Projectors**

Description	Part ID	D1	Weight (kg)
PC1 114-133/60 Pole clamp, single (Ø 114-133)	139-2708	114-133	1.40




PC2 82-109/60 Pole camp, double (Ø 82-109)	139-2705	82-109	1.10
--	----------	--------	------



**Projectors**

Description	Part ID	D1	Weight (kg)
PC1 82-109/60 Pole camp, single (Ø 82-109)	139-2704	82-109	1.10



**Control****DMX Controller**

Description	Part ID
DMX Controller	400-0469

**DMX Controller (smart)**

Description	Part ID	Additional information
DMX Controller (smart)	400-0470	IP20. The Touch Panel is an untutive abd easy-to use keypad or one DMX universe. It can store up to 36 scences; alternatively, via ....



**Projectors****DMX Booster Box**

Description	Part ID
DMX Booster Box	400-0474

**DMX Motion Sensor**

Description	Part ID
DMX Motion Sensor	400-0478



**DMX Termination Plug**

Description	Part ID
DMX Termination Plug	400-0475

**DMX Plug and Socket**

Description	Part ID
DMX Plug and Socket	400-0479



**DMX Combination Cable**

Description	Part ID
DMX Combination Cable	400-0480

**DMX Wireless Repeater**

Description	Part ID
DMX Wireless Repeater	400-0477



**DMX Wireless Transceiver**

Description	Part ID
DMX Wireless Transceiver	400-0476

**DMX Wireless Antenna**

Description	Part ID
Antenna RF5dB	430-0036
Antenna RF1.8dB	430-0018