

Description





IP66. Class I. IK07. Marine-grade, die-cast aluminum alloy. 5CE superior corrosion protection including PCS hardware. Silicone CCG® Controlled Compression Gasket. Safety glass lens. CAD-optimized optics for superior illumination and glare control. Integral driver in thermally separated compartment. OLC® One LED Concept. Factory-installed LED circuit board. 0-10V Dimming comes standard with luminaire. Luminaire is factory-sealed and does not need to be opened during installation.

Specify product with 7 Digit product code - Finish Color.
Accessories, such as mounting, optical, and electrical, must be specified separately.
Example: XXX-XXXX-9004 (Black)
+ XXX-XXXX (Accessory 1)

Floodlights

Specifications

Material description

| | |
|----------------------|--|
| Body | Marine-grade, die-cast aluminium alloy |
| Lens | Safety glass lens |
| Colors |  RAL9004 Black  RAL9007 Grey Metallic  RAL9016 White  RAL8019 Dark Bronze |
| Gasket | Silicone rubber gaskets |
| Fasteners | PCS polymer coated stainless steel |
| Ingress protection | IP66 |
| Impact resistance | IK07 |
| Corrosion resistance | 5CE |

Electrical description

| | |
|------------------|----------------------------------|
| Power supply | 120-277V / 50-60 Hz |
| Driver / Ballast | Integral EC electronic converter |

Additional information

| | |
|----------|---|
| Lifetime | LED >60,000 h Ta 25°(L70/B10) Control gear >50,000 h Ta 25° |
| Listings | ETL, UL-1598, CSA-C22.2#250.0. Suitable for Wet Locations. |

Options

Light distribution



symmetric, very narrow beam [VN]



symmetric, very narrow beam, 'sharp cut-off' [VNS]



symmetric, medium beam [M]




wallwash

Color temperature



3000 K







4000 K

Nominal Watt

8 W

Configurations

| Light distribution | Part ID | Light source | Delivered lumens | Rated input power | CRI | Weight (lb) |
|---|-------------------|----------------------------|------------------|-------------------|-----|-------------|
| symmetric, medium beam [M]  | 145-9791 | LED-3/6W / 700 mA - 3000 K | 590.6 | 7.7 W | 80 | 3.5 |
| | 145-9795 | LED-3/6W / 700 mA - 4000 K | 590.6 | 7.7 W | 80 | 3.5 |
| symmetric, very narrow beam [VN]  | 145-9792 | LED-3/6W / 700 mA - 3000 K | 552 | 7.7 W | 80 | 3.5 |
| | 145-9796 | LED-3/6W / 700 mA - 4000 K | 552 | 7.7 W | 80 | 3.5 |
| symmetric, very narrow beam, 'sharp cut-off' [VNS]  | 145-9793 | LED-3/6W / 700 mA - 3000 K | 594.4 | 7.7 W | 80 | 3.5 |
| | 145-9797 | LED-3/6W / 700 mA - 4000 K | 594.4 | 7.7 W | 80 | 3.5 |
| wallwash  | 145-9791+145-9846 | LED-3/6W / 700 mA - 3000 K | 388.6 | 7.7 W | 80 | 3.5 |
| | 145-9795+145-9846 | LED-3/6W / 700 mA - 4000 K | 388.6 | 7.7 W | 80 | 3.5 |