


## Floodlights

**Description**

IP66. Class I. IK07. Marine-grade, die-cast aluminum alloy. 5CE superior corrosion protection including PCS hardware. Silicone CCG® Controlled Compression Gasket. Safety glass lens. CAD-optimized optics for superior illumination and glare control. Integral driver in thermally separated compartment. OLC® One LED Concept. Factory-installed LED circuit board. 0-10V Dimming comes standard with luminaire. Luminaire is factory-sealed and does not need to be opened during installation.

Specify product with 7 Digit product code - Finish Color. Accessories, such as mounting, optical, and electrical, must be specified separately.  
Example: XXX-XXXX-9004 (Black)  
+ XXX-XXXX (Accessory 1)

## Floodlights

---

### Specifications

#### Material description

---

|                      |  |
|----------------------|--|
| Body                 | Marine-grade, die-cast aluminium alloy   |
| Lens                 | Safety glass lens  |
| Colors               |  RAL9004 Black<br> RAL9007 Grey Metallic<br> RAL9016 White<br> RAL8019 Dark Bronze |
| Gasket               | Silicone rubber gaskets  |
| Fasteners            | PCS polymer coated stainless steel   |
| Ingress protection   | IP66   |
| Impact resistance    | IK07   |
| Corrosion resistance | 5CE  |

---

#### Electrical description

---

|                  |                                  |
|------------------|----------------------------------|
| Power supply     | 120-277V / 50-60 Hz              |
| Driver / Ballast | Integral EC electronic converter |

---

#### Additional information

---

|          |   |
|----------|---|
| Lifetime | LED >60,000 h Ta 25°(L70/B10) Control gear >50,000 h Ta 25° |
| Listings | ETL, UL-1598, CSA-C22.2#250.0. Suitable for Wet Locations.  |

---

## Floodlights

## Options

## Light distribution



symmetric, very narrow beam [VN]



symmetric, very narrow beam, 'sharp cut-off' [VNS]



symmetric, medium beam [M]



wallwash

## Color temperature



3000 K







4000 K

8 W

## Floodlights

## Configurations

| Light distribution  | Part ID           | Light source               | Delivered lumens | Rated input power | CRI | Weight (lb) |
|---|-------------------|----------------------------|------------------|-------------------|-----|-------------|
| symmetric, medium beam [M]<br>                          | 145-9791          | LED-3/6W / 700 mA - 3000 K | 590.6            | 7.7 W             | 80  | 3.5         |
|   | 145-9795          | LED-3/6W / 700 mA - 4000 K | 590.6            | 7.7 W             | 80  | 3.5         |
| symmetric, very narrow beam [VN]<br>                    | 145-9792          | LED-3/6W / 700 mA - 3000 K | 552              | 7.7 W             | 80  | 3.5         |
|   | 145-9796          | LED-3/6W / 700 mA - 4000 K | 552              | 7.7 W             | 80  | 3.5         |
| symmetric, very narrow beam, 'sharp cut-off' [VNS]<br> | 145-9793          | LED-3/6W / 700 mA - 3000 K | 594.4            | 7.7 W             | 80  | 3.5         |
|   | 145-9797          | LED-3/6W / 700 mA - 4000 K | 594.4            | 7.7 W             | 80  | 3.5         |
| wallwash<br>  | 145-9791+145-9846 | LED-3/6W / 700 mA - 3000 K | 388.6            | 7.7 W             | 80  | 3.5         |
|   | 145-9795+145-9846 | LED-3/6W / 700 mA - 4000 K | 388.6            | 7.7 W             | 80  | 3.5         |