

Description

IP66. Class I. IK07. Marine-grade, die-cast aluminum alloy. 5CE superior corrosion protection including PCS hardware. Silicone CCG® Controlled Compression Gasket. Safety glass lens. CAD-optimized optics for superior illumination and glare control. OLC® One LED Concept. Factory-installed LED circuit board. 0-10V Dimming comes standard with luminaire. Luminaire is factory-sealed and does not need to be opened during installation.

Knuckle permits 350° horizontal and 90° vertical aiming of optics.

Specify product with 7 Digit product code - Finish Color. Accessories, such as mounting, optical, and electrical, must be specified separately.

Example: XXX-XXXX-9004 (Black)

+ XXX-XXXX (Accessory 1)



Specifications Material description

Body Marine-grade, die-cast aluminium alloy

Lens Safety glass lens

Colors RAL9004 Black

RAL9007 Grey Metallic

RAL9016 White

RAL8019 Dark Bronze

Gasket Silicone CCG® Controlled Compression Gasket

Fasteners PCS Polymer Coated Stainless Steel Hardware

Ingress protection IP66
Corrosion resistance 5CE

Electrical description

Power supply Integral [ECG] electronic driver 120V-277V. 0-10V dimmable, to be specified with order.

Driver / Ballast Integral EC electronic converter, thermally separated

Additional information



Options Light distribution



symmetric, wide beam [W]

•

symmetric, medium beam [M]



symmetric, very narrow beam [VN]



symmetric, very narrow beam, 'sharp cut-off' [VNS]



wallwash



linear spread, very narrow beam [VN]



linear spread, very narrow beam, 'sharp cut-off'

Color temperature Nominal Watt

56 W

3000 K

4000K



Configurations

Light distribution	Part ID	Light source	Delivered lumens	Rated input power	CRI	Weight (lb)
linear spread, very narrow beam [VN]	146-6002+146-0439	LED-24/48W / 700 mA - 3000 K	5545.2	54 W	80	20.00
•	146-6003+146-0439	LED-24/48W / 700 mA - 4000 K	5927.6	54 W	80	20.00
linear spread, very narrow beam,	146-6004+146-0439	LED-24/48W / 700 mA - 3000 K	6104.9	54 W	80	20.00
'sharp cut-off' +	146-6005+146-0439	LED-24/48W / 700 mA - 4000 K	6526	54 W	80	20.00
symmetric, medium beam [M]	146-6000	LED-24/48W / 700 mA - 3000 K	6047.2	54 W	80	20.00
	146-6001	LED-24/48W / 700 mA - 4000 K	6464.2	54 W	80	20.00
symmetric, very narrow beam [VN]	146-6002	LED-24/48W / 700 mA - 3000 K	5986.1	54 W	80	20.00
	146-6003	LED-24/48W / 700 mA - 4000 K	6398.9	54 W	80	20.00
symmetric, very narrow beam, 'sharp	146-6004	LED-24/48W / 700 mA - 3000 K	6442.7	54 W	80	20.00
cut-off' [VNS]	146-6005	LED-24/48W / 700 mA - 4000 K	6887	54 W	80	20.00
symmetric, wide beam [W]	146-6006	LED-24/48W / 700 mA - 3000 K	5388.5	54 W	80	20.00
	146-6007	LED-24/48W / 700 mA - 4000 K	5760.1	54 W	80	20.00
wallwash	146-6000+146-0646	LED-24/48W / 700 mA - 3000 K	4851.9	54 W	80	20.00
	146-6001+146-0646	LED-24/48W / 700 mA - 4000 K	5186.6	54 W	80	20.00

FLC141 LED - Ceon



Floodlights

Light distribution	Part ID	Light source	Delivered lumens	Rated input power	CRI	Weight (lb)






Optical Accessories

Glare shield

Description	Part ID	Α	C1
Glare shield ES	146-0229	4.72	5.71



FLC141 LED - Ceon



Floodlights

Snoot

Description	Part ID	Α	C1
Snoot ET	146-0398	4.72	5.70

