

### Description

IP66, Class I. Class II on request. IK07. Marine-grade, die-cast aluminium alloy. 5CE superior corrosion protection including PCS hardware. Silicone CCG® Controlled Compression Gasket. Safety glass lens. Two cable entries. Integral EC electronic converter in thermally separated compartment. Darklight anodised aluminium reflector for superior illumination and glare control. Factory-installed LED circuit board. Tunable White Technology. DALI Interface. The luminaire is factory-sealed and does not need to be opened during the installation.

Suitable for mounting up to max. 40 mm ceiling thickness. A pre-installation blockout, proud or flush, is available and recommended for mounting in concrete ceilings. To be ordered separately.

A maximum of one internal optical accessory.

The luminaire is not suitable for chlorine containing environments e.g. swimming pool. Special version suitable for chlorine containing environments, on request. Must be specified at time of ordering.

**Ceiling luminaires****Specifications****Material description**

---

Body	Marine-grade, die-cast aluminium alloy
Lens	Safety glass lens
Colours	 RAL9004 Signal black  RAL9006 White aluminium  RAL9007 Grey aluminium  RAL7016 Anthracite grey  RAL9016 Traffic white
Gasket	Silicone CCG® Controlled Compression Gasket
Fasteners	PCS Polymer Coated Stainless Steel Hardware
Ingress protection	IP66
Impact resistance	IK07
Corrosion resistance	5CE

---

**Electrical description**

---

Power supply	220-240V / 50-60 Hz
Driver / Ballast	DALI
Power factor	> 0.9

---

**Additional information**

---

Lifetime	Ta=25° L70B50 > 50000h
Energy efficiency class	E (Light source)

---

**Options****Light distribution**

symmetric, wide beam [B]

2700-6000K

**Nominal Watt**

0 W

24 W






symmetric, medium beam [M]




symmetric, narrow beam [E]

**Configurations**


Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI	Weight (kg)
symmetric, medium beam [M] 	134-1812	LED-FT-24W / 700mA - 2700-6000 K	1826.2	27 W	80	2.80
symmetric, narrow beam [E] 	134-1814	LED-FT-24W / 700mA - 2700-6000 K	946.5	27 W	80	2.80
symmetric, wide beam [B] 	134-1810	LED-FT-24W / 700mA - 2700-6000 K	1856.5	27 W	80	2.80

**Ceiling luminaires****Mounting Accessories****Installation breakout, proud**

Description	Part ID	A	B	C1	D1
BD014-I	134-1763	443	324	192	216


**Installation breakout, flush with shadow line**

Description	Part ID	A	B	C1	D1	D2
BD014-III	134-1764	443	324	192	216	267



**Optical Accessories****Linear spread lens**


Description	Part ID	C1
IO-180-DOC140-LED-FT	134-1816	171



— C1 —

**Flood lens**


Description	Part ID	C1
IO-360-DOC140-LED-FT	134-1818	171



— C1 —

**Wallwash lens**

Description	Part ID	C1
IO-20-WW-DOC140-LED-FT	134-1817	171



— C1 —