

### Description

IP66. IK07. Marine-grade, die-cast aluminium alloy, with polished stainless steel frame. 5CE superior corrosion protection including PCS hardware. Polycarbonate main lens. Silicone rubber gasket. Luminaire is factory-sealed and does not need to be opened during installation. Factory-installed with 30 cm of flexible halogen-free cable.

Integral EC electronic converter. Advanced thermal management protects LEDs while optimising lumens output. One cable entry. Second cable entry for through wiring available on request.


# STO134 LED Shallow Depth - Stainless Steel

**we-ef**

## Wall luminaires recessed

### Specifications

#### Material description

Body	Marine-grade, die-cast aluminium alloy with polished stainless steel frame
Lens	Polycarbonate
Colours	 Stainless Steel
Gasket	Silicone rubber gasket
Fasteners	PCS hardware
Ingress protection	IP66
Impact resistance	IK07
Corrosion resistance	5CE

#### Electrical description

Power supply	220-240V / 50-60 Hz
Driver / Ballast	Integral EC electronic converter





#### Additional information

# STO134 LED Shallow Depth - Stainless Steel



Wall luminaires recessed

## Options


Light distribution	Colour temperature	Nominal Watt
 diffused distribution	 3000 K	0 W
	 4000 K	
	 2700 K	

# STO134 LED Shallow Depth - Stainless Steel



Wall luminaires recessed

## Configurations

Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI	Weight (kg)
diffused distribution 	190-9013	LED-5W / 250 mA - 3000 K	78.6	5.6 W	80	0.95
	190-9058	LED-5W / 250 mA - 4000 K	81.7	5.6 W	80	0.95
	190-9063	LED-5W / 250 mA - 2700 K	75.4	5.6 W	80	0.95