

#### **Description**

IP66, Class I. IK07. Marine-grade, die-cast aluminium alloy. 5CE superior corrosion protection + primer including PCS hardware. Polycarbonate main lens. Silicone rubber gasket. Luminaire is factory-sealed and does not need to be opened during installation. Factory-installed with 30 cm of flexible halogen-free cable.

Integral EC electronic converter. Advanced thermal management protects LEDs while optimising lumens output. One cable entry.



#### Wall luminaires recessed

# **Specifications Material description**

Body Marine-grade, die-cast aluminium alloy

Lens Polycarbonate

Colours RAL9004 Signal black

RAL9006 White aluminium
RAL9007 Grey aluminium

Gasket Silicone rubber gasket

Fasteners PCS Polymer Coated Stainless Steel Hardware (unpainted)

Ingress protection IP66
Impact resistance IK07

Corrosion resistance 5CE+Primer

#### **Electrical description**

Power supply 230V / 50 Hz

Driver / Ballast Integral EC electronic converter

#### **Additional information**

Warranty	The product is supplied with 10-year warranty. Please refer to the LED Warranty Statement
	located on www.we-ef.com for further details.

### **STL134 LED Reduced Depth**




#### Wall luminaires recessed

### **Options**

### Light distribution Colour temperature Nominal Watt





0 W

# **STL134 LED Reduced Depth**



#### Wall luminaires recessed

# **Configurations**

Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI	Weight (kg)
Shielded	190-9042	LED-6W / 350 mA - 3000 K	25.2	8 W	80	0.80
	190-9046	LED-6W / 350 mA - 4000 K	26.6	8 W	80	0.80
	190-9050	LED-6W / 350 mA - 2700 K	23.8	8 W	80	0.80