
Wall luminaires recessed





Description

IP66, Class I. IK10. Marine-grade, die-cast aluminium alloy. 5CE superior corrosion protection + primer including PCS hardware. Polycarbonate main lens. Silicone rubber gasket. Luminaire is factory-sealed and does not need to be opened during installation. Factory-installed with 30 cm of flexible halogen-free cable.

Integral EC electronic converter. Advanced thermal management protects LEDs while optimising lumens output. One cable entry.

Wall luminaires recessed

Specifications Material description

Body Marine-grade, die-cast aluminium alloy

Lens Polycarbonate

Colours RAL9004 Signal black

RAL9006 White aluminium
RAL9007 Grey aluminium

Gasket Silicone rubber gasket

Fasteners PCS Polymer Coated Stainless Steel Hardware (unpainted)

Ingress protection IP66
Impact resistance IK10

Corrosion resistance 5CE+Primer

Electrical description

Power supply 230V / 50 Hz

Driver / Ballast Integral EC electronic converter

Additional information

Warranty	The product is supplied with 10-year warranty. Please refer to the LED Warranty Statement
	located on www.we-ef.com for further details.

STI134 LED Reduced Depth




Wall luminaires recessed

Options

Light distribution Colour temperature Nominal Watt





0 W

STI134 LED Reduced Depth



Wall luminaires recessed

Configurations

Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI	Weight (kg)
floor wash	190-9043	LED-6W / 350 mA - 3000 K	170.9	8 W	80	0.90
	190-9047	LED-6W / 350 mA - 4000 K	180.7	8 W	80	0.90
	190-9051	LED-6W / 350 mA - 2700 K	161.1	8 W	80	0.90