

### Description

RGBW Colour Changer. IP67. Class I. IK10+. Stainless steel construction including PCS hardware. Safety glass lens, max. load 5 tonnes. Luminaire can be driven over at low speed. Silicone rubber gasket. Anti-wick technology, equipped with a cable gland and 0.5 meters of flexible, PVC-free cable.

Integral EC electronic converter. Advanced thermal management protects LEDs while optimising lumens output. Removable LED boards for upgrading. CAD-optimised optics for superior illumination and glare control. OLC® One LED Concept. 20° tiltable and 355° rotatable. LED circuit board with WE-EF Colour Boost Technology. DMX Interface. For other control interface options to suit specific project requirements, contact WE-EF.

Luminaire installation blackout and sealable junction box included in supply.

**IMPORTANT!** Inground blockouts must be installed with effective drainage, watch [here](https://vimeo.com/672613058).

### Specifications

#### Material description

---

Body	Stainless steel construction
Lens	Safety glass lens, max. load 5 tonnes
Colours	 Stainless Steel
Gasket	Silicone rubber gasket
Fasteners	PCS hardware
Ingress protection	IP67
Impact resistance	IK10+

---

#### Electrical description

---

Power supply	220-240V / 50-60 Hz
Driver / Ballast	Integral EC electronic converter with DMX Interface
Termination	Junction box supplied

---

#### Additional information

---

Warranty	
Warranty	The product is supplied with 10-year warranty. Please refer to the LED Warranty Statement located on <a href="http://www.we-ef.com">www.we-ef.com</a> for further details. Warranty void if installed without proper drainage.

---

### Options

#### Light distribution



symmetric, wide beam [B]



symmetric, medium beam [M]



#### Colour temperature

RGBW

#### Nominal Watt

0 W

**Configurations**

Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI	Weight (kg)
symmetric, medium beam [M] 	185-7805	LED-12/25W - RGBW	2053.3	26 W	20/80	12.00
symmetric, wide beam [B] 	185-7804	LED-12/25W - RGBW	2059.3	26 W	20/80	12.00


**Mounting Accessories**

**Installation cover**

---

Description	Part ID	C1
Installation cover BE	185-0326	300

---




**Inground luminaires**

---

**Optical Accessories****Optical Adaptor**


Description	Part ID
Internal optical Adaptor IA	185-7419



---

**Linear spread lens**

Description	Part ID	C1
Linear spread lens IO-180	185-7581	149




**Inground luminaires**

---

**Surface wash lens**

Description	Part ID	C1
Flood lens IO-360	185-7582	149



---

**Linear louvre**

Description	Part ID	C1
Linear louvre IL	185-9568	149



**Control****DMX Wireless Antenna**

Description	Part ID
Antenna RF1.8dB	430-0018
Antenna RF5dB	430-0036

**DMX Wireless Repeater**

Description	Part ID
DMX Wireless Repeater	400-0477



### DMX Wireless Transceiver

Description	Part ID
DMX Wireless Transceiver	400-0476

