


## Inground luminaires

**Description**

RGBW Colour Changer. IP67, Class I. IK10+. Stainless steel construction including PCS hardware. Safety glass lens; max. load 5 tonnes. Luminaire can be driven over at low speed. Silicone rubber gasket. Factory-sealed termination chamber complete with cable gland and 0.5 m of flexible PVC free cable.

Integral EC electronic converter. Advanced thermal management protects LEDs while optimising lumens output. Removable LED boards for upgrading. CAD-optimised optics for superior illumination and glare control. OLC\_R\_One LED Concept. LED circuit board with WE-EF Colour Boost Technology. DMX Interface. For other control interface options to suit specific project requirements, contact WE-EF.

Luminaire installation blockout and sealable junction box included in supply.

**IMPORTANT!** Inground blockouts must be installed with effective drainage, watch **[here](https://vimeo.com/672613058)**.

**Inground luminaires****Specifications****Material description**

Body	Stainless steel construction
Lens	Safety glass lens, max. load 5 tonnes
Colours	 Stainless Steel
Gasket	Silicone rubber gasket
Fasteners	PCS Polymer Coated Stainless Steel Hardware (unpainted)
Ingress protection	IP67
Impact resistance	IK10+

**Electrical description**

Power supply	230V / 50 Hz
Driver / Ballast	Integral EC electronic converter with DMX Interface
Termination	Junction box supplied

**Additional information**

Warranty	The product is supplied with 10-year warranty. Please refer to the LED Warranty Statement located on <a href="http://www.we-ef.com">www.we-ef.com</a> for further details. Warranty void if installed without proper drainage.
----------	--

**Options****Light distribution**

symmetric, wide beam [B]



symmetric, medium beam [M]



symmetric, wallgrazer [A6]




**Colour temperature****Nominal Watt**

RGBW/4K

0 W


## Inground luminaires

## Configurations

Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI	Weight (kg)
symmetric, medium beam [M]	185-7793	LED-12/19W - RGBW/4K	1326.7	23 W	20/80	6.40
						
symmetric, wallgrazer [A6]	185-7884	LED-12/19W - RGBW/4K	1445.5	32 W	20/80	6.40
						
symmetric, wide beam [B]	185-7792	LED-12/19W - RGBW/4K	1330.6	23 W	20/80	6.40
						

**Mounting Accessories****Installation cover**


Description	Part ID	C1
Installation cover BE	185-0325	250



— C1 —

**Optical Accessories****Linear spread lens**


Description	Part ID	C1
Linear spread lens IO-180	185-7170	191



C1

**Surface wash lens**


Description	Part ID	C1
Flood lens IO-360	185-7171	191



C1

**Wallwash lens**

Description	Part ID	C1
IO-20-WW-ETC/EVC_30-FS-LED	185-8492	191



**Control****DMX Wireless Antenna**

Description	Part ID
Antenna RF1.8dB	430-0018
Antenna RF5dB	430-0036

**DMX Wireless Repeater**

Description	Part ID
DMX Wireless Repeater	400-0477



**DMX Wireless Transceiver**

Description	Part ID
DMX Wireless Transceiver	400-0476

