

### Description

RGBW Colour Changer. IP69. IK10+. Stainless steel construction including PCS hardware. Safety glass lens; max. load 5 tonnes. Luminaire can be driven over at low speed. Silicone rubber gasket. Anti-wick technology, equipped with a cable gland and 0.5 meters of flexible, PVC-free cable.

Integral EC electronic converter. Advanced thermal management protects LEDs while optimising lumens output. Removable LED boards for upgrading. CAD-optimised optics for superior illumination and glare control. OLC® One LED Concept. LED circuit board with WE-EF Colour Boost Technology. DMX Interface. For other control interface options to suit specific project requirements, contact WE-EF.

Luminaire installation blackout and sealable junction box included in supply.

## Inground luminaires

---

### Specifications

#### Material description

---

Body	Stainless steel construction
Lens	Safety glass lens, max. load 5 tonnes
Colours	 RAL9007 Grey aluminium
Gasket	Silicone rubber gasket
Fasteners	PCS hardware
Ingress protection	IP69
Impact resistance	IK10+

---

#### Electrical description

---

Driver / Ballast	Integral EC electronic converter with DMX Interface
------------------	---

---

#### Additional information

### Options

#### Light distribution



symmetric, wide beam [B]



symmetric, medium beam [M]



symmetric, wallgrazer [A6]



#### Colour temperature

RGBW/4K

#### Nominal Watt

0 W


**Configurations**

Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI	Weight (kg)
symmetric, medium beam [M] 	185-7799	LED-12/19W - RGBW/4K	1326.7	23 W	20/80	6.40
symmetric, wallgrazer [A6] 	185-7896	LED-12/19W - RGBW/4K	2699.8	34 W	20/80	6.40
symmetric, wide beam [B] 	185-7798	LED-12/19W - RGBW/4K	1330.6	23 W	20/80	6.40

**Mounting Accessories**


**Installation cover**

Description	Part ID	C1
Installation cover BE	185-0325	250




**Inground luminaires****Optical Accessories****Linear spread lens**

Description	Part ID	C1
Linear spread lens IO-180	185-7170	191

**Flood lens**

Description	Part ID	C1
Flood lens IO-360	185-7171	191



**Inground luminaires**

---

**Linear louvre**


Description	Part ID	C1
Linear louvre IL	185-7172	191



---

**Honeycomb louvre**

Description	Part ID	C1
Honeycomb Louvre IW	185-7180	191




## Inground luminaires

---

### Wallwash lens

Description	Part ID	C1
Wallwash lens IO-20	134-1492	191



C1

**Control****DMX Wireless Antenna**

Description	Part ID
Antenna RF1.8dB	430-0018

**DMX Wireless Repeater**

Description	Part ID
DMX Wireless Repeater	400-0477



### DMX Wireless Transceiver

Description	Part ID
DMX Wireless Transceiver	400-0476

