


## ETC340-FS CC LED

### Inground luminaires

**we-ef**



#### Description

RGBW Colour Changer. IP69. IK10+. Stainless steel construction including PCS hardware. Safety glass lens; max. load 5 tonnes. Luminaire can be driven over at low speed. Silicone rubber gasket. Factory-sealed termination chamber complete with cable gland and 0.5 m of flexible PVC free cable.

Integral EC electronic converter. Advanced thermal management protects LEDs while optimising lumens output. Removable LED boards for upgrading. CAD-optimised optics for superior illumination and glare control. OLC® One LED Concept. LED circuit board with WE-EF Colour Boost Technology. DMX Interface. For other control interface options to suit specific project requirements, contact WE-EF.

Luminaire installation blackout and sealable junction box included in supply.


#### WE-EF LIGHTING (Thailand) Co., Ltd.

57 Moo 5, Kingkaew Rd., Bangplee, 10540 Samutprakarn - Phone: +66 2 738 96 20 - Fax: +66 2 738 96 29

<https://we-ef.com/asia>

Subject to technical changes and errors. - Generated on 16/08/2025

**Specifications****Material description**

Body	Stainless steel construction
Lens	Safety glass lens, max. load 5 tonnes
Colours	 Stainless Steel
Gasket	Silicone rubber gasket
Fasteners	PCS hardware
Ingress protection	IP69
Impact resistance	IK10+

**Electrical description**

Power supply	230V / 50 Hz
Driver / Ballast	Integral EC electronic converter with DMX Interface
Termination	Junction box supplied

**Additional information**



Warranty	The product is supplied with 10-year warranty. Please refer to the LED Warranty Statement located on <a href="http://www.we-ef.com">www.we-ef.com</a> for further details.
----------	----------------------------------------------------------------------------------------------------------------------------------------------------------------------------

ETC340-FS CC LED



Inground luminaires

Options




Light distribution	Colour temperature	Nominal Watt
 symmetric, wide beam [B]	RGBW	0 W
 symmetric, medium beam [M]		
 symmetric, wallgrazer [A6]		

# ETC340-FS CC LED

Inground luminaires

**we-ef**

## Configurations

Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI	Weight (kg)
symmetric, medium beam [M] 	185-7811	LED-48/30W - RGBW	2463.8	32 W	20/80	11.00
symmetric, wallgrazer [A6] 	185-7890	LED-48/30W - RGBW	2223.3	32 W	20/80	11.00
symmetric, wide beam [B] 	185-7810	LED-48/30W - RGBW	2376.9	32 W	20/80	11.00

**WE-EF LIGHTING (Thailand) Co., Ltd.**

57 Moo 5, Kingkaew Rd., Bangplee, 10540 Samutprakarn - Phone: +66 2 738 96 20 - Fax: +66 2 738 96 29


<https://we-ef.com/asia>

Subject to technical changes and errors. - Generated on 16/08/2025

Mounting Accessories


Installation cover

Description	Part ID	C1
Installation cover BE	185-0326	300




**Optical Accessories****Flood lens**

Description	Part ID	C1
Flood lens IO-360	185-7579	220


**Linear spread lens**

Description	Part ID	C1
Linear spread lens IO-180	185-7580	220



Wallwash lens

Description	Part ID	C1
Wallwash lens IO-20	185-7589	220



# ETC340-FS CC LED

Inground luminaires

**we-ef**

## Control

### DMX Wireless Antenna

Description	Part ID
Antenna RF1.8dB	430-0018

### DMX Wireless Repeater

Description	Part ID
DMX Wireless Repeater	400-0477



**WE-EF LIGHTING (Thailand) Co., Ltd.**

57 Moo 5, Kingkaew Rd., Bangplee, 10540 Samutprakarn - Phone: +66 2 738 96 20 - Fax: +66 2 738 96 29

<https://we-ef.com/asia>

Subject to technical changes and errors. - Generated on 16/08/2025

DMX Wireless Transceiver

Description	Part ID
DMX Wireless Transceiver	400-0476

