


Inground luminaires

**Description**

Tunable white. IP67. IK10+. Stainless steel construction including PCS hardware. Safety glass lens, max. load 5 tonnes. Luminaire can be driven over at low speed. Silicone rubber gasket. Anti-wick technology, equipped with a cable gland and 0.5 meters of flexible, PVC-free cable.

Integral EC electronic converter. Advanced thermal management protects LEDs while optimising lumens output. Removable LED boards for upgrading. CAD-optimised optics for superior illumination and glare control. OLC® One LED Concept. 20° tiltable and 355° rotatable. LED circuit board with Tunable White Technology. DALI Interface. For other control interface options to suit specific project requirements, contact WE-EF.

Luminaire installation blockout and sealable junction box included in supply.

IMPORTANT! Inground blockouts must be installed with effective drainage, watch **[here](https://vimeo.com/672613058)**.

Inground luminaires**Specifications****Material description**

Body	Stainless steel construction
Lens	Safety glass lens, max. load 5 tonnes
Colours	 Stainless Steel
Gasket	Silicone rubber gasket
Fasteners	PCS hardware
Ingress protection	IP67
Impact resistance	IK10+

Electrical description

Driver / Ballast	Integral EC electronic converter with DALI Interface
------------------	--

Additional information


Warranty	The product is supplied with 10-year warranty. Please refer to the LED Warranty Statement located on www.we-ef.com for further details. Warranty void if installed without proper drainage.
----------	--

Options**Light distribution****Colour temperature****Nominal Watt**

symmetric, wide beam [B]



2200-6000K

0 W




symmetric, medium beam [M]

Inground luminaires**Configurations**

Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI	Weight (kg)
symmetric, medium beam [M] 	185-7802	LED-12/28W / 420 mA - 2200-6000 K	2625	32 W	80	12.00
symmetric, wide beam [B] 	185-7801	LED-12/28W / 420 mA - 2200-6000 K	2511.9	32 W	80	12.00

Mounting Accessories**Installation cover**


Description	Part ID	C1
Installation cover BE	185-0326	300



C1

Optical Accessories**Linear spread lens**


Description	Part ID	C1
Linear spread lens IO-180	185-7581	149



C1

Surface wash lens

Description	Part ID	C1
Flood lens IO-360	185-7582	149



C1

Inground luminaires**Linear louvre**

Description	Part ID	C1
Linear louvre LL	185-9568	149

