**Description**

Tunable white inground. IP67, Class I. IK10+. Stainless steel construction including PCS hardware. Safety glass lens; max. load 5 tonnes. Luminaire can be driven over at low speed. Silicone rubber gasket. Factory-sealed termination chamber complete with cable gland and 0.5 m of flexible PVC free cable.

Integral EC electronic converter. Advanced thermal management protects LEDs while optimising lumens output. Removable LED boards for upgrading. CAD-optimised optics for superior illumination and glare control. OLC\_R\_ One LED Concept. LED circuit board with Tunable White Technology. DALI Interface . For other control interface options to suit specific project requirements, contact WE-EF.

Luminaire installation blockout and sealable junction box included in supply.

IMPORTANT! Inground blockouts must be installed with effective drainage, watch [here](https://vimeo.com/672613058).

**Inground luminaires**

---

**Specifications****Material description**

---

Body	Stainless steel construction
Lens	Safety glass lens, max. load 5 tonnes
Colours	 Stainless Steel
Gasket	Silicone rubber gasket
Fasteners	PCS hardware
Ingress protection	IP67
Impact resistance	IK10+

---

**Electrical description**

---

Driver / Ballast	Integral EC electronic converter with DALI Interface
------------------	--

---

**Additional information**

---

Warranty	The product is supplied with 10-year warranty. Please refer to the LED Warranty Statement located on <a href="http://www.we-ef.com">www.we-ef.com</a> for further details. Warranty void if installed without proper drainage.
----------	--

---

### Options

#### Light distribution



symmetric, wide beam [B]



symmetric, medium beam [M]



symmetric, wallgrazer [A6]

#### Colour temperature




2200-6000K

#### Nominal Watt

0 W

## Inground luminaires

## Configurations

Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI	Weight (kg)
symmetric, medium beam [M] 	185-7790	LED-12/19W - 2200-6000 K	2012	23 W	80	6.40
symmetric, wallgrazer [A6] 	185-7883	LED-12/19W - 2200-6000 K	1702.1	34 W	80	6.40
symmetric, wide beam [B] 	185-7789	LED-12/19W - 2200-6000 K	1758.3	34 W	80	6.40


**Mounting Accessories**

**Installation cover**

---

Description	Part ID	C1
Installation cover BE	185-0325	250

---



**Inground luminaires**


**Optical Accessories**

**Linear spread lens**

---

Description	Part ID	C1
Linear spread lens IO-180	185-7170	191

---




---

**Surface wash lens**

---

Description	Part ID	C1
Flood lens IO-360	185-7171	191

---




## Inground luminaires

---

### Wallwash lens

Description	Part ID	C1
IO-20-WW-ETC/EVC_30-FS-LED	185-8492	191



C1

---