


## Inground luminaires

**Description**

Tunable white inground. IP67, Class I. IK10+. Stainless steel construction including PCS hardware. Safety glass lens; max. load 5 tonnes. Luminaire can be driven over at low speed. Silicone rubber gasket. Factory-sealed termination chamber complete with cable gland and 0.5 m of flexible PVC free cable.

Integral EC electronic converter. Advanced thermal management protects LEDs while optimising lumens output. Removable LED boards for upgrading. CAD-optimised optics for superior illumination and glare control. OLC\_R\_ One LED Concept. LED circuit board with Tunable White Technology. DALI Interface . For other control interface options to suit specific project requirements, contact WE-EF.

Luminaire installation blockout and sealable junction box included in supply.

**IMPORTANT!** Inground blockouts must be installed with effective drainage, watch **[here](https://vimeo.com/672613058)**.

**Inground luminaires****Specifications****Material description**

Body	Stainless steel construction
Lens	Safety glass lens, max. load 5 tonnes
Colours	 Stainless Steel
Gasket	Silicone rubber gasket
Fasteners	PCS hardware
Ingress protection	IP67
Impact resistance	IK10+

**Electrical description**


Driver / Ballast	Integral EC electronic converter with DALI Interface
------------------	--

**Additional information**

Warranty	The product is supplied with 10-year warranty. Please refer to the LED Warranty Statement located on <a href="http://www.we-ef.com">www.we-ef.com</a> for further details. Warranty void if installed without proper drainage.
----------	--

**Options****Light distribution**

symmetric, wide beam [B]



symmetric, medium beam [M]



symmetric, wallgrazer [A6]




**Colour temperature**

2200-6000K

**Nominal Watt**


0 W

## Configurations

Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI	Weight (kg)
symmetric, medium beam [M] 	185-7790	LED-12/19W - 2200-6000 K	2012	23 W	80	6.40
symmetric, wallgrazer [A6] 	185-7883	LED-12/19W - 2200-6000 K	1702.1	34 W	80	6.40
symmetric, wide beam [B] 	185-7789	LED-12/19W - 2200-6000 K	1758.3	34 W	80	6.40

**Mounting Accessories****Installation cover**


Description	Part ID	C1
Installation cover BE	185-0325	250



C1

**Optical Accessories****Linear spread lens**


Description	Part ID	C1
Linear spread lens IO-180	185-7170	191



C1

**Surface wash lens**

Description	Part ID	C1
Flood lens IO-360	185-7171	191



C1

**Wallwash lens**

Description	Part ID	C1
IO-20-WW-ETC/EVC_30-FS-LED	185-8492	191

