

Description

Tunable white. IP69. IK10+. Stainless steel construction including PCS hardware. Safety glass lens; max. load 5 tonnes. Luminaire can be driven over at low speed. Silicone rubber gasket. Anti-wick technology, equipped with a cable gland and 0.5 meters of flexible, PVC-free cable.

Integral EC electronic converter. Advanced thermal management protects LEDs while optimising lumens output. Removable LED boards for upgrading. CAD-optimised optics for superior illumination and glare control. OLC® One LED Concept. LED circuit board with Tunable White Technology. DALI Interface. For other control interface options to suit specific project requirements, contact WE-EF.

Luminaire installation blackout and sealable junction box included in supply.

Inground luminaires

Specifications

Material description

Body	Stainless steel construction
Lens	Safety glass lens, max. load 5 tonnes
Colours	 Stainless Steel
Gasket	Silicone rubber gasket
Fasteners	PCS hardware
Ingress protection	IP69
Impact resistance	IK10+

Electrical description

Driver / Ballast	Integral EC electronic converter with DALI Interface
------------------	------------------------------------------------------

Additional information

Inground luminaires

Options

Light distribution

Colour temperature

Nominal Watt



symmetric, wide beam [B]

2200-6000K

0 W






symmetric, medium beam [M]



symmetric, wallgrazer [A6]


Configurations

Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI	Weight (kg)
symmetric, medium beam [M] 	185-7796	LED-12/19W - 2200-6000 K	2012	23 W	80	6.40
symmetric, wallgrazer [A6] 	185-7895	LED-12/19W - 2200-6000 K	1702.1	22 W	80	6.40
symmetric, wide beam [B] 	185-7795	LED-12/19W - 2200-6000 K	1926.5	23 W	80	6.40

Mounting Accessories


Installation cover

Description	Part ID	C1
Installation cover BE	185-0325	250




Inground luminaires**Optical Accessories****Linear spread lens**

Description	Part ID	C1
Linear spread lens IO-180	185-7170	191

**Flood lens**

Description	Part ID	C1
Flood lens IO-360	185-7171	191



Inground luminaires


Linear louvre

Description	Part ID	C1
Linear louvre IL	185-7172	191



Honeycomb louvre


Description	Part ID	C1
Honeycomb Louvre IW	185-7180	191



Inground luminaires

Wallwash lens

Description	Part ID	C1
Wallwash lens IO-20	134-1492	191



C1