


Inground luminaires

**Description**

Tunable white inground. IP67, Class I. IK10+. Stainless steel construction including PCS hardware. Safety glass lens; max. load 5 tonnes. Luminaire can be driven over at low speed. Silicone rubber gasket. Factory-sealed termination chamber complete with cable gland and 0.5 m of flexible PVC free cable.

Integral EC electronic converter. Advanced thermal management protects LEDs while optimising lumens output. Removable LED boards for upgrading. CAD-optimised optics for superior illumination and glare control. OLC_R_ One LED Concept. LED circuit board with Tunable White Technology. DALI Interface . For other control interface options to suit specific project requirements, contact WE-EF.

Luminaire installation blockout and sealable junction box included in supply.

IMPORTANT! Inground blockouts must be installed with effective drainage, watch **here.**

Inground luminaires**Specifications****Material description**

Body	Stainless steel construction
Lens	Safety glass lens, max. load 5 tonnes
Colours	 Stainless Steel
Gasket	Silicone rubber gasket
Fasteners	PCS hardware
Ingress protection	IP67
Impact resistance	IK10+

Electrical description

Driver / Ballast	Integral EC electronic converter with DALI Interface
------------------	------------------------------------------------------

Additional information

Warranty	The product is supplied with 10-year warranty. Please refer to the LED Warranty Statement located on www.we-ef.com for further details. Warranty void if installed without proper drainage.
----------	--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Options**Light distribution**

symmetric, wide beam [B]



symmetric, medium beam [M]



symmetric, wallgrazer [A6]

Colour temperature




2200-6000K

Nominal Watt

0 W


Inground luminaires

Configurations

Light distribution	Part ID	Light source	Rated lumens	Rated input power	CRI	Weight (kg)
symmetric, medium beam [M]	185-7808	LED-24/30W / 225 mA - 2200-6000 K	2975	34 W	80	11.00
						
symmetric, wallgrazer [A6]	185-7889	LED-24/30W / 225 mA - 2200-6000 K	2699.8	34 W	80	11.00
						
symmetric, wide beam [B]	185-7807	LED-24/30W / 225 mA - 2200-6000 K	2846.8	34 W	80	11.00
						

Mounting Accessories**Installation cover**


Description	Part ID	C1
Installation cover BE	185-0326	300



C1

Optical Accessories**Surface wash lens**


Description	Part ID	C1
Flood lens IO-360	185-7579	220



C1

Linear spread lens

Description	Part ID	C1
Linear spread lens IO-180	185-7580	220



C1

Wallwash lens

Description	Part ID	C1
Wallwash lens IO-20	185-7589	220

