ZFT430 LED





Description

IP66, Class I. Class II on request. IK09. Marine-grade, die-cast aluminium alloy. 5CE superior corrosion protection including PCS hardware. Silicone CCG® Controlled Compression Gasket. PMMA main lens. Integral EC electronic converter in thermally separated compartment. DALI. CAD-optimised OLC® One LED Concept optics for superior illumination and glare control. Factory installed LED circuit board. The luminaire is factory-sealed and does not need to be opened during installation.


Optional 2200 K version available. To be specified at time of ordering.


Light distribution rectangular, side throw [R65] Light source LED-9/27W / 1050 mA - 4000 K CRI 80 Power supply EC LEDs 9 Rated input power 29 W Nominal Lumen (Im) LED Lumen 450 Total Lumen 4050 Tj 85 Rated lumens (Im) LED Lumen 382.2 Total Lumen 3439.5 Ta 25	Weight	5.50 kg				
CRI 80 Power supply EC LEDs 9 Rated input power 29 W Nominal Lumen (Im) LED Lumen 450 Total Lumen 4050 Tj 85 Rated lumens (Im) LED Lumen 382.2 Total Lumen 3439.5	Light distribution	rectangular, side throw [R65]				
Power supply EC LEDs 9 Rated input power 29 W Nominal Lumen (Im) LED Lumen 450 Total Lumen 4050 Tj 85 Rated lumens (Im) LED Lumen 382.2 Total Lumen 3439.5	Light source	LED-9/27W / 1050 mA - 4000 K				
LEDs 9 Rated input power 29 W Nominal Lumen (Im) LED Lumen 450 Total Lumen 4050 Tj 85 Rated lumens (Im) LED Lumen 382.2 Total Lumen 3439.5	CRI	80				
Rated input power 29 W Nominal Lumen (Im) LED Lumen 450 Total Lumen 4050 Tj 85 Rated lumens (Im) LED Lumen 382.2 Total Lumen 3439.5	Power supply	EC				
Nominal Lumen (Im) LED Lumen 450 Total Lumen 4050 Tj 85 Rated lumens (Im) LED Lumen 382.2 Total Lumen 3439.5	LEDs	9				
LED Lumen 450 Total Lumen 4050 Tj 85 Rated lumens (lm) LED Lumen 382.2 Total Lumen 3439.5	Rated input power	29 W				
Total Lumen 4050 Tj 85 Rated lumens (lm) LED Lumen 382.2 Total Lumen 3439.5	Nominal Lumen (lm)					
Tj 85 Rated lumens (lm) LED Lumen 382.2 Total Lumen 3439.5	LED Lumen	450				
Rated lumens (lm) LED Lumen 382.2 Total Lumen 3439.5	Total Lumen	4050				
LED Lumen 382.2 Total Lumen 3439.5	Tj	85				
Total Lumen 3439.5	Rated lumens (lm)					
	LED Lumen	382.2				
Ta 25	Total Lumen	3439.5				
	Та	25				

115-1441

ZFT430 LED







Specifications Material description

Body Marine-grade, die-cast aluminium alloy

Lens PMMA

Colours RAL9004 Signal black

RAL9006 White aluminium

RAL9007 Grey aluminium

RAL7016 Anthracite grey

RAL9016 Traffic white

Gasket Silicone CCG® Controlled Compression Gasket

Fasteners PCS Polymer Coated Stainless Steel Hardware

Ingress protection IP66
Impact resistance IK09
Corrosion resistance 5CE

Windage 0.104 m²

Electrical description

Power supply 220-240V / 50-60 Hz

Driver / Ballast Integral EC electronic converter. DALI

Power factor > 0.9

Surge protection 6/6 kV (optional SP10)

Fagerhult Lighting Ltd

115-1441

ZFT430 LED



Additional information

Lifetime $Ta=25^{\circ} L90B10 > 90000h$

115-1441

ZFT430 LED



Control

Eco Step Dim® Basic

Description	Part ID
Eco Step Dim® Basic LED	430-0001

Eco Step Dim® Advanced

Description	Part ID
Eco Step Dim® Advanced LED	430-0002


ZFT430 LED



Mounting Accessories

Wall and pole brackets RZ

Description	Part ID	C1	D1	D2	D × L1	M1	Weight (kg)
RZO-400 Wall bracket, single	115-1324	277	231	195	76 x 80	12	3.50



RZ2-400 Pole bracket, double	115-1323	258	76 x 100	4.90
------------------------------	----------	-----	----------	------

