we-ef

KTY234 LED II



Description

IP66. Class I. IK10. Marine-grade, all aluminum construction. 5CE superior corrosion protection including PCS hardware. Silicone CCG® Controlled Compression Gasket. Polycarbonate lens, CAD-optimized indirect optics for superior illumination and glare control. Integral driver in thermally separated compartment. Factory-installed LED circuit board. 0-10V Dimming comes standard with luminaire.

Luminaire spacing up to 35 ft; ideal for pathway lighting applications.

Specify product with 7 Digit product code - Finish Color. Accessories, such as mounting, optical, and electrical, must be specified separately.


Example: XXX-XXXX-9004 (Black)


+ XXX-XXXX (Accessory 1)

| Weight | 19.80 lb |
|--|------------------------------|
| Light distribution | symmetric distribution [C60] |
| Light source | LED-6/26W / 1400 mA - 4000 K |
| CRI | 80 |
| Power supply | electronic gear |
| BUG | B1 U3 G1 |
| LEDs | 6 |
| Rated input power | 29 W |
| Nominal Lumen (lm) | |
| Nominal Edine (IIII) | |
| LED Lumen | 575 |
| | 575 3450 |
| LED Lumen | |
| LED Lumen Total Lumen | 3450 |
| LED Lumen Total Lumen Tj | 3450 |
| LED Lumen Total Lumen Tj Rated lumens (lm) | 3450 85 |

KTY234 LED II







Specifications Material description

Body Marine-grade all-aluminum construction

0.35"

Lens Polycarbonate

Colors RAL9004 Black

RAL9007 Grey Metallic

RAL9016 White

RAL8019 Dark Bronze

Gasket Silicone CCG® Controlled Compression Gasket

Fasteners PCS Polymer Coated Stainless Steel Hardware

Ingress protection IP66
Impact resistance IK10
Corrosion resistance 5CE

Electrical description

Power supply Integral [ECG] electronic driver 120V-277V. 0-10V dimmable, to be specified with order.

Driver / Ballast Integral EC electronic converter
Surge protection Integral 10kV Surge Protector

WE-EF LIGHTING USA, LLC

KTY234 LED II



Additional information

| Id=23 /40 L70D IO / 700001 | Lifetime | Ta=25°/40° L90B10 > 90000h |
|----------------------------|----------|----------------------------|
|----------------------------|----------|----------------------------|

Lead Time This is a new product release and may have an extended lead time.

BUG Rating Please see individual Spec Sheets for classification of Backlight, Uplight and Glare.

Listings ETL, UL-1598, CSA-C22.2#250.0. Suitable for Wet Locations.


KTY234 LED II



Mounting Accessories

Planted root

| Description | Part ID | D1 | D2 | D3 | D4 | H1 | H2 | M1 | Weight (lb) |
|-------------------|----------|------|------|------|------|-------|-------|-----|-------------|
| Planted root ESV4 | 300-0461 | 5.71 | 5.12 | 4.01 | 4.25 | 15.75 | 13.78 | .31 | 15.50 |




KTY234 LED II



Optical Accessories

Light shield

| Description | Part ID | H1 | Weight (lb) |
|-------------------------------|----------|------|-------------|
| LS180 KTY (factory installed) | 114-9185 | 2.59 | 0.04 |



114-9094 KTY234 LED II

WE-EF LIGHTING USA, LLC

410-D Keystone Drive, 15086 Warrendale, PA 15086 Phone: +1 724 742 0030

> customersupport.usa@we-ef.com https://we-ef.com/us

Subject to technical changes and errors.

Generated on 10/23/2024

