



Description

IP67. IK10+. Stainless steel construction including PCS hardware. Safety glass lens, max. load 5 tonnes. Luminaire can be driven over at low speed. Silicone rubber gasket. Anti-wick technology, equipped with a cable gland and 0.5 meters of flexible, PVC-free cable.

Integral EC electronic converter. Advanced thermal management protects LEDs while optimising lumens output. Removable LED boards for upgrading. CAD-optimised optics for superior illumination and glare control. OLC® One LED Concept. 20° tiltable and 355° rotatable. 1-10 V analogue dimming or DALI interface available on request.


Luminaire installation blockout and sealable junction box included in supply.


ASC Anti Slip Coating on request.

IMPORTANT! Inground blockouts must be installed with effective drainage, watch here.

Light distribution symmetric, very narrow beam [EE] Light source LED-12/36W / 1050 mA - 4000 K CRI 80 Power supply EC LEDs 12 Rated input power 40 W Nominal Lumen (Im) LED Lumen 450 Total Lumen 5400 Tj 85 Rated lumens (Im) LED Lumen 357 Total Lumen 4283.6 Ta 25	Weight	12.00 kg
CRI 80 Power supply EC LEDs 12 Rated input power 40 W Nominal Lumen (Im) LED Lumen 450 Total Lumen 5400 Tj 85 Rated lumens (Im) LED Lumen 357 Total Lumen 4283.6	Light distribution	
Power supply EC LEDs 12 Rated input power 40 W Nominal Lumen (Im) LED Lumen 450 Total Lumen 5400 Tj 85 Rated lumens (Im) LED Lumen 357 Total Lumen 4283.6	Light source	LED-12/36W / 1050 mA - 4000 K
LEDs 12 Rated input power 40 W Nominal Lumen (Im) LED Lumen 450 Total Lumen 5400 Tj 85 Rated lumens (Im) LED Lumen 357 Total Lumen 4283.6	CRI	80
Rated input power 40 W Nominal Lumen (Im) LED Lumen 450 Total Lumen 5400 Tj 85 Rated lumens (Im) LED Lumen 357 Total Lumen 4283.6	Power supply	EC
Nominal Lumen (Im) LED Lumen 450 Total Lumen 5400 Tj 85 Rated lumens (Im) LED Lumen 357 Total Lumen 4283.6	LEDs	12
LED Lumen 450 Total Lumen 5400 Tj 85 Rated lumens (lm) LED Lumen 357 Total Lumen 4283.6	Rated input power	40 W
Total Lumen 5400 Tj 85 Rated lumens (lm) LED Lumen 357 Total Lumen 4283.6	Nominal Lumen (lm)	
Tj 85 Rated lumens (lm) LED Lumen 357 Total Lumen 4283.6	LED Lumen	450
Rated lumens (lm) LED Lumen 357 Total Lumen 4283.6	Total Lumen	5400
LED Lumen 357 Total Lumen 4283.6	Tj	85
Total Lumen 4283.6	Rated lumens (lm)	
	LED Lumen	357
Ta 25	Total Lumen	4283.6
	Та	25







Specifications

Material description

Body Stainless steel construction

Lens Safety glass lens, max. load 5 tonnes

Colours

Stainless Steel

Gasket Silicone rubber gasket

Fasteners PCS Polymer Coated Stainless Steel Hardware (unpainted)

Ingress protection IP67
Impact resistance IK10+

Electrical description

Power supply 230V / 50 Hz

Driver / Ballast Integral EC electronic converter

Termination Junction box supplied

Additional information

Warranty	The product is supplied with 10-year warranty. Please refer to the LED Warranty Statement
	located on www.we-ef.com for further details. Warranty void if installed without proper
	drainage.






Mounting Accessories

Installation cover

Description	Part ID	C1
Installation cover BE	185-0326	300







Optical Accessories

Optical Adaptor

Description	Part ID
Internal optical Adaptor IA	185-7419



Linear spread lens

Description	Part ID	C1
Linear spread lens IO-180	185-7581	149






ETC340-GB LED

Surface wash lens

Description	Part ID	C1	
Flood lens IO-360	185-7582	149	



Linear louvre

Description	Part ID	C1	
Linear louvre IL	185-9568	149	



185-7782



ETC340-GB LED

Colour filter

Description	Part ID	
Colour filter IF	on request	

